

CF-F9 Central Extractor Filter. CF-HEPA H13/W3 Central Extractor Filter.

CF-F9. Light Welding/Soldering Fume and light Dust.

CF-F9 is made for light welding/soldering fume and light dust. It is equipped with a 12m2 F9 Filter Cartridge and a built in Fan with aluminium impeller. The legs are 0.5m. The air volume at the diameter 200mm inlet is ca.1400m3/h.

CF-HEPA H13/W3. Light Stainless Steel welding.

CF-HEPA H13/W3 is equipped with a HEPA H13/W3 (9m2) Filter Box with an Alu-Mesh Prefilter (washable). The Unit can be used for light stainless steel welding/soldering.

Replacement Filter Cartridge.

It is time to put in a Replacement Filter when the extraction doesn't catch the smoke or dust in a satisfactoring way. It just takes a few minutes to change.

Capacity.

4-8 Flexa/Chemikus Extraction Arms (d. 75-100mm) can be connected to a CF Central Extractor Filter or 1-2 Flexi Extraction Arms (d. 160mm)

The inlet diameter is 200mm. Use d.200mm Vertical/Horizontal ducting from the CF and go down with 75/100mm ducts to the Flexa/Chemikus Extraction Arms and d.160mm duct to Flexi Arms. Ask our specialists for advice.



40 Years Experience!

40 Years Experience of design and manufacturing at your service!

The Plymoth products are a combination of well-proven technique and progressive new ideas.

Plymoth is always a step ahead - but not expensive!

	Art. No.
CF-F9. ~1/1.1kW/220V/50Hz. F9 Filter(12m2). Inlet 200mm. 4 Legs (0.5m).	P-963
CF-F9. ~3/1.1kW/400V/50Hz. F9 Filter(12m2). Inlet 200mm. 4 Legs (0.5m)	P-964
CF-HEPA H13/W3. ~1/1.1Kw/220V/50Hz. H13/W3 Filter(9m2). Inlet 200mm. 4 Legs (0.5m)	P-965
CF-HEPA H13/W3. ~3/1.1Kw/400V/50Hz. H13/W3 Filter(9m2). Inlet 200mm. 4 Legs (0.5m)	P-966
F9 Replacement Filter Cartridge 12m2. For MF, CF-F9, MF-Filter Tables (High).	P-160
HEPA H13/W3 Filter Box 9m2. For MF, CF-F9, CF-HEP. (400x505x200mm).	P-577

J. Plymoth AB, Trarydsallén 4E, 287 72 TRARYD, Sweden.
Tel.: +46 40 700 15 · E-Mail: info@plymoth.com · www.plymoth.com