

## NX-6000/8000 without Fan. For Coolant/Oil Mist.

### Coolant or Oil Mist.

NX mechanical oil mist filter is designed to eliminate coolant or oil mist from lathing, milling, drilling, sawing, water cutting etc.

### Filter Cassettes.

NX-6000/8000 oil mist filters are equipped with self-draining filter cassettes of nailed glass-fiber and HEPA H13 filters. Each filter has a separate pressure gauge (manometer). Over 99,95% filter efficiency is achieved. The cleaned air can be re-circulated into the premises. Keeps heating costs down.

### Application.

NX 6000 is for 2-10 machines. NX 8000 is for 4-12 machines.

### Complete Unit without Fan.

NX-6000/8000 is a complete unit of powder coated steel sheet with 3+3/2+2 nailed glass-fiber filter cassettes and 3/2 HEPA H13 filters. Inlet from left or right with inlet flange with inside measure D.400 mm and cover for the not used inlet. Oil return pipe with 1 inch outside thread. The NX filters without fan shall be connected to a separate fan or a central extraction system. The outlet flange has inside D.400mm.



|   | <b>Art.Nr.</b> |
|---|----------------|
| <b>NX-6000 Filter <u>without Fan</u> for Coolant and Oil Mist</b> incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 400mm (inside measure), 3 filter cassettes of nailed glass-fiber 10m <sup>2</sup> each and 3 which are 8m <sup>2</sup> each, 3 HEPA H13 filters 22m <sup>2</sup> each and 9 pcs pressure gauges(manometers).<br><b>Measurements: 2000x2100x750mm.</b>   | P-635          |
| <b>NX-8000 Filter <u>without Fan</u> for Coolant and Oil Mist</b> incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 400mm (inside measure), 2 filter cassettes of nailed glass-fiber 21m <sup>2</sup> each and 2 which are 15m <sup>2</sup> each, 2 HEPA H13 filters 44 m <sup>2</sup> each and 6 pcs pressure gauges(manometers).<br><b>Measurements: 2000x2100x900mm.</b> | P-639          |
| <b>Replacement Nailed Glass-Fiber Filter Cassette (10m<sup>2</sup> EU-5). First from the bottom for NX-2000/6000 (NX-6000 3 pcs).</b>   | P-318          |
| <b>Replacement Nailed Glass-Fiber Filter Cassette (8m<sup>2</sup> EU-5/9). Second from the bottom for NX-2000/6000 (NX-6000 3 pcs). This cassette is used as the only cassette for NX-1000.</b>   | P-319          |
| <b>Replacement Nailed Glass-Fiber Filter Cassette (21 m<sup>2</sup> EU-5). First from the bottom for NX-4000/8000 (NX-8000 2 pcs).</b>  | P-320          |
| <b>Replacement Nailed Glass-Fiber Filter Cassette (15 m<sup>2</sup> EU-9). Second from the bottom for NX-4000/8000 (NX-8000 2pcs).</b>  | P-321          |
| <b>Replacement HEPA H13 Filter 22m<sup>2</sup> (99,95%) for NX-1000/2000/6000 (NX-6000 3 pcs).</b>  | P-264          |
| <b>Replacement HEPA H13 Filter 44m<sup>2</sup> (99,95%) for NX- 4000/8000 (NX-8000 2 pcs).</b>  | P-266          |