










Accessories for Extractor Arms and Extractor Cranes

| | | Art. Nr. | Art.Nr. |
|---|---|-------------------|----------|
| | | d.160 mm | d.200 mm |
|  | Turning Flange for Hose. When connecting an Extractor Crane with a d.160 mm or d.200 mm hose to a central extraction system it is recommended to use a turning flange between the fixed ducting at the wall and the hose. | P-030 | P-031 |
|  | Suspension Shackle with turning joint. Max. hanging weight 60 kg. Fits the first horizontal arm of Extractor Cranes and Support Arms (not Herkules). Incl. suspension shackle with turning joint, carbine hook and M10/90mm bolt with nut. | Art. Nr. P-050 | |
|  | C-Profile 30/30/10/2 mm for Extractor Cranes and Suspension Arms which have a first Horizontal Support arm with a length of 1.3-3m. | Art. Nr. | Art. Nr. |
| | | 1.3 m | 2.3 m |
| | | P-027 | P-028 |
| | | 3 m | P-029 |
|  | Suspension Trolley with 4 Ball Bearing Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 60 kg weight. Incl. trolley with 4 ball bearing wheels. | P-023 | |
|  | Suspension Trolley with plastic Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 10 kg weight. Incl. trolley with 2 plastic wheels, S-hook and a sling. | P-024 | |
|  | Extension Hose with Magnetic Hood Diameter 160 mm. Two magnets. | Art. Nr. | Art.Nr. |
| | | 2 m | 3 m |
| | | P-017 | P-018 |
|  | Floor/Ceiling Stanchions for: Flexi 1.5-5 m, Super-Max SMSV and Pro-Flex PRSV | Art. Nr. | Art. Nr. |
| | | 0.5 m | 0.75 m |
| | | P-427 | P-428 |
| | | 1 m | 1.25 m |
| | | P-021 | P-429 |
| | | 1.5 m | P-430 |
| | | 1.75 m | 2 m |
| | | P-431 | P-022 |
| | | 2.25 m | 2,5 m |
| | | P-432 | P-433 |
|  | Floor/Ceiling Stanchions for: Super-Max 1.5-4 m and Pro-Flex 2-4 m. | Art. Nr. | Art. Nr. |
| | | 0.5 m | 0.75 m |
| | | P-434 | P-435 |
| | | 1 m | 1.25 m |
| | | P-083 | P-436 |
| | | 1.5 m | P-437 |
| | | 1.75 m | 2 m |
| | | P-438 | P-084 |
| | | 2.25 m | 2.5 m |
| | | P-439 | P-440 |
|  | Halogen Lamp Cartridge 20 Watt/12 Volt. For d.125/160 mm Hoods (Flexi Hoods, Pro-Flex Hoods and Super-Max Hoods) | P-019 | |
| | Halogen Lamp Cartridge 20 Watt/12 Volt. For d.200 mm Hoods (Flexi Hoods, Pro-Flex Hoods and Super-Max Hoods) | P-081 | |
| | Transformer 220/12 Volt for Halogen Lamp Cartridge above. | P-020 | |