

## NX-2000/4000 without Fan. For Collant/Oil Mist.

## Coolant or Oil Mist.

NX mechanical oil mist filter is designed to eliminate coolant or oil mist from lathing, milling, drilling, sawing, water cutting etc. **Filter Cassettes.** 

NX-2000/4000 oil mist filters are equipped with two self-draining filter cassettes of nailed glass-fiber and a HEPA H13 filter. Each filter has a separate pressure gauge (manometer). Over 99,95% filter efficiency is achieved. The cleaned air can be re-circulated into the premises. Keeps heating costs down.

## Application.

NX-2000 for 1-4 machines. NX-4000 for 1-8 machines. **Complete Unit without Fan.** 

NX is a complete unit of powder coated steel sheet with 2 nailed glass-fiber filter cassettes and HEPA filter. Inlet from left or right with inlet flange with inside measure D.200 mm (NX-2000) and D.315 mm (NX-4000). Cover for the not used inlet. Oil return pipe with 1 inch outside thread. The NX-2000/4000 oil mist filters without fan shall be connected to a separate fan or a central extraction system. The outlet flange has an inside measurement of D.200 mm (NX-2000) and D.315 mm (NX-4000).

## **Accessories**

As accessory you can get 0.5 m Extension Legs.



|   | Art.Nr. |
|---|---------|
| <b>NX-2000 Filter without Fan for Coolant and Oil Mist</b> incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with | P-631   |
| 200mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet   |         |
| flange 200mm (inside measure), 2 filter cassettes of nailed glass-fiber, 10m2 (10+10m2)   |         |
| and 8 m2 (8+8+8 m2), HEPA H13 filter 22m2 and 3 pcs pressure gauges (manometers).   |         |
| Measurements: 1600x640x750mm.   |         |
| NX-4000 Filter without Fan for Coolant and Oil Mist incl. filterbox and legs of powder  | P-633   |
| painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with   |         |
| 315mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet   |         |
| flange 315mm (inside measure), 2 filter cassettes of nailed glass-fiber, 21 m2 (21+21 m2)   |         |
| and 15 m2 (15+15+15 m2), HEPA-filter 44 m2 and 3 pcs pressure gauges(manometers).   |         |
| Measurements: 1600x800x900mm.   |         |
| Extension Legs 0.5 m (4 pcs.) for NX-1000/2000/4000   | P-322   |
| Replacement Nailed Glass-Fiber Filter Cassette (10m <sup>2</sup> EU-5). First from the bottom for   | P-318   |
| <b>NX-2000/6000</b> (NX-6000 3 pcs).  |         |
| Replacement Nailed Glass-Fiber Filter Cassette (8m <sup>2</sup> EU-5/9). Second from the bottom   | P-319   |
| for NX-2000/6000 (NX-6000 3 pcs). This cassette is the only needed for NX-1000.   |         |
| Replacement Nailed Glass-Fiber Filter Cassette (21 m <sup>2</sup> EU-5). First from the bottom for  | P-320   |
| NX- <b>4000/8000</b> (NX-8000 2 pcs).   |         |
| Replacement Nailed Glass-Fiber Filter Cassette (15 m <sup>2</sup> EU-9). Second from the bottom   | P-321   |
| for <b>NX-4000/8000</b> (NX-8000 2 pcs).  |         |
| Replacement HEPA H13 Filter 22m <sup>2</sup> (99,95%) for NX-1000/2000/6000 (NX-6000 3 pcs)   | P-264   |
| Replacement HEPA H13 Filter 44m <sup>2</sup> (99,95%) NX- 4000/8000 (NX-8000 2 pcs).  | P-266   |