

NX-400/600


Oil-and Coolant mist.

NX-400 and NX-600 are filters for extraction of oil-and coolant mist from lathes, milling machines, drilling machines and other machines with the same problems.

Easy to get started

The NX filters are complete units with filter, fan, silencer and adjustable inlet damper. Holders for wall mounting or hanging from the ceiling are built in. Can also be equipped with legs for mounting standing on the machine.

Just attach a diameter 160mm hose between the bottom of the NX filter and the machine. Plug it into a socket. Adjust the built in damper so just the mist will be exhausted. Lock the damper with the locking screw. The filtered liquid will drop back to the machine through the inlet hose.



Five step – 99.99% efficiency

1) Inlet “Splash” plate. 2) Expansion chamber. 3) Labyrinth filter. 4) “Long Life” nailed glassfiber filter cassette with aluminum separators. 5) HEPA filter H13.



30 Years experience!

30 years experience from design and manufacturing of products for a better working environment.

	Art. No.
NX-400. 1-phase/0.37kw/220v/50Hz. Start/Stop. 4m cable. 450(W)x450(D)x850mm(H).	P-588
NX-400. 3-phase/0.37kw/440v/50Hz. 450(W)x450(D)x850mm(H)	P-590
NX-600. 1-phase/0.75kw/220v/50Hz. Start/Stop.4m cable. 510(W)x560(D)x850mm(H).	P-592
NX-600. 3-phase/0.75kw/440v/50Hz. 510(W)x560(D)x850mm(H).	P-594
HEPA filter for NX-400. H13(6m2). 350(W)x420(D)x200mm(H).	P-595
HEPA filter for NX-600. H13 (9m2). 430(W)x490(D)x 200mm(H).	P-596
Legs 0.2m. 4pcs.	P-597
Legs 0.4m. 4 pcs.	P-598
Exchange filter cassette for NX-400. Nailed glassfiber with Al. separators (3+3m2).	P-599
Exchange filter cassette for NX-600. Nailed glassfiber with Al. separators (4.5+4.5m2)	P-600