

Wall-Flex Cartridge Filter

Dust and Fumes

Plymoth Wall-Flex cartridge filters are designed for use with Flexi extractor arms. With up to 99% efficiency they clean the premises of welding fumes, lighter grinding dust etc. The cleaned air is recirculated into the premises, with no heat loss at all.

Replaceable Cartridge

Filtration of pollutants is carried out in two stages. Access to the maintenance-free, replaceable cartridge filter is easy and changing it takes just a couple of minutes. An activated carbon filter for gases is also available. A carbon filter holder is then needed (P-085).

Wallbracket and Fan

Wall-Flex is as standard equipped with a strong wallbracket. The fan is to be mounted on the top side and Flexi FLT extractor arms on the bottom side of the filter box. No unnecessary holes have to be made in the wall! Wall-Flex can be connected to a central extraction system. A d.160 mm outlet adaptor is included.



	Art. Nr.	Art. Nr. d.160 mm	Art. Nr. d.200 mm
Wall-Flex filter box with. 12 m ² filter cartridge	P-026		
Fan P-Max 2100 TURBO / 0.75 kW / 3-Phase	P-013		
Fan P-Max 2100 TURBO / 0.75 kW / 1-Phase 220 Volt	P-015		
Replacement filter cartridge 12 m ²	P-160		
Holder for activated carbon filter	P-085		
Activated carbon filter for WF. 10 pcs.	P-107		
Flexi FLT 1.5 m.		P-051	P-056
Flexi FLT 2 m.		P-052	P-057
Flexi FLT 3 m.		P-053	P-058
Flexi Horizontal 4 m. Wallbracket incl.		P-009	P-145
Flexi Horizontal 5 m. Wallbracket incl.		P-010	P-146
Accessories: see leaflet "Accessories,"			