

## NX-6000/8000 with Fan for Coolant/Oil Mist.

### Coolant or Oil Mist.

NX mechanical oil mist filter is designed to eliminate coolant or oil mist from lathing, milling, drilling, sawing, water cutting etc.



### Filter Cassettes.

NX-6000/8000 oil mist filters are equipped with 3/2 self-draining Filter Cassettes of Nailed Glass-Fiber and 3/2 HEPA H13 Filters. Each filter has a separate pressure gauge (manometer). Over 99,95% filter efficiency. The cleaned air can be re-circulated into the premises. Keeps heating costs down.

### Application.

NX-6000 is for 2-10 machines. NX-8000 is for 4-12 machines.

### Complete Unit

NX is a complete unit of powdercoated steel sheet with Filter Cassettes, HEPA H13 Filters and Fans. Inlet from left or right with inlet flange with inside measure D.400 mm and cover for the not used inlet. Oil return pipe with 1 inch outside thread.

	<b>Art.Nr.</b>
<b>NX-6000 Filter with 3 Fans 3-phase/3x2,2 kW/400V50Hz for Coolant and Oilmist</b> incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with 400mm inlet flange ( inside measure) and cover plate for the not used inlet side, fans 3-phase/3x2,2 kW/400V/50Hz, 3+3 filter cassettes of nailed glass-fiber (3x10m <sup>2</sup> ) and (3x8m <sup>2</sup> ), HEPA H13 filter 3x22m <sup>2</sup> and 9 pcs pressure gauges. <b>Measurements: 2100x2100x750mm.</b>	P-636
<b>NX-8000 Filter with 2 Fans 3-phase/2x4 kW/400V/50Hz for Coolant and Oilmist</b> incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1"outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, 2 fans 3-phase/2x4 kW/400V/50Hz, 2+2 filter cassettes of nailed glass-fiber (2x21 m <sup>2</sup> ) and (2x15 m <sup>2</sup> ), HEPA H13 filter 2x44m <sup>2</sup> and 6 pcs pressure gauges. <b>Measurements: 2100x1700x900mm</b>	P-640
<b>Replacement Filter Cassette of Nailed Glass-Fiber (10m<sup>2</sup> EU-5).</b> First from the bottom for NX-2000/6000 (NX-6000 3 pcs).	P-318
<b>Replacement Filter Cassette of Nailed Glass-Fiber (8m<sup>2</sup> EU-5/9) Second from the bottom for NX-2000/6000</b> (NX-6000 3 pcs). Is used as the only cassette for NX-1000.	P-319
<b>Replacement Filter Cassette of Nailed Glass-Fiber (21 m<sup>2</sup> EU-5)</b> First from the bottom for NX-4000/8000 (NX-8000 2 pcs).	P-320
<b>Replacement Filter Cassette of Nailed Glass-Fiber (15 m<sup>2</sup> EU-9)</b> Second from the bottom for NX-4000/8000 (NX-8000 2pcs).	P-321
<b>Replacement HEPA H13 Filter 22m<sup>2</sup> (99,95%) for NX-1000/2000/6000</b> (NX-6000 3 pcs).	P-264
<b>Replacement HEPA H13 Filter 44m<sup>2</sup> (99,95%) for NX-4000/8000</b> (NX-8000 2 pcs).	P-266