

NX-400/600 for Coolant/Oil Mist.

Oil-and Coolant mist.


NX-400 and NX-600 are Extractor Filters for extraction of oil-and coolant mist from lathes, milling machines, drilling machines and other machines with the same problems.

Easy to get started

The NX filters are complete units with filter, fan, silencer and adjustable inlet damper. Holders for wall mounting or hanging from the ceiling are built in. Can also be equipped with legs for mounting standing on the machine.

Simple Installation.

Just attach a diameter 160mm hose between the bottom of the NX filter and the machine. Plug it into a socket. Adjust the built in damper so just the mist will be exhausted. Lock the damper with the locking screw. The filtered liquid will drop back to the machine through the inlet hose.



Five steps – 99.95% Efficiency.

1) Inlet “plash” plate. 2) Expansion chamber. 3) Labyrinth filter. 4) “Long Life” nailed Glass-Fiber Filter Cassette with Aluminum Separators. 5) HEPA H13 Filter (To be ordered separately).



40 Years experience!

40 years experience from design and manufacturing of products for a better working environment.

| | Art. No. |
|---|----------|
| NX-400/1-phase/0.37kw/220v/50Hz. Start/Stop. 4m cable. 450(W)x450(D)x850mm(H). | P-588 |
| NX-400/3-phase/0.37kw/440v/50Hz. 450(W)x450(D)x850mm(H). | P-590 |
| NX-600/1-phase/0.75kw/220v/50Hz. Start/Stop.4m cable. 510(W)x560(D)x850mm(H). | P-592 |
| NX-600. 3-phase/0.75kw/440v/50Hz. 510(W)x560(D)x850mm(H). | P-594 |
| HEPA H13 Filter for NX-400 H13(6m2). 350(W)x420(D)x200mm(H). | P-595 |
| HEPA H13 Filter for NX-600 H13 (9m2). 430(W)x490(D)x 200mm(H). | P-596 |
| Legs 0.2m. 4pcs. | P-597 |
| Legs 0.4m. 4 pcs. | P-598 |
| Replacement Filter Cassette NX-400.Nailed Glass-Fiber with Alu Separators (3+3m2). | P-599 |
| Replacement Filter Cassette NX-600.Nailed Glass-Fiber with Alu Separators (4.5+4.5m2). | P-600 |

J.Plymoth AB, Trarydsallén 4E, 287 72 TRARYD, Sweden

Tel.: ++46 40 700 15, E-Mail: info@plymoth.com, www.plymoth.com