

Mobi-Oil 2m/3m

Oil-and Coolant mist.

Mobi-oil is a Mobile Extractor-Filter for extraction of oil-and coolant mist from lathes, milling machines, drilling machines or other machines with the same problems.

Easy to use.

Move the Mobi-Oil to the machine. Plug it into an electric socket and start to use it. The super flexible Extraction-Arm 2m or 3m (Order separately) makes it very simple to put the hood into the right position. Adjust the damper in the hood so just the mist is exhausted. No bad air or slippery floors any longer.

Liquid Containers.

The filtered liquid is collected at the bottom of the Mobi-Oil in 2 plastic containers. You can see from the outside when a container is full. Then just move the hose, which is equipped with a quick connector, to the empty one. No down time! Then empty the full container and put it back. The liquid can normally be reused in the machine.



Five Step Filtration - 99.95% Efficiency.

1) Inlet "Splash Plate". 2) Expansion Chamber. 3) Labyrinth Filter. 4) Long Life nailed Glass-fiber Cassette with Alu Separators. 5) HEPA H13 FILTER. (1-3 can be cleaned).

	Art. No.
Mobi-Oil. 1-phase/0.75kW/220V/50Hz. Start/stop. 4m Cable with Plug. All Filters included. 4 Heavy Duty Castors with Brakes. 550mm(W)x780mm(D)x1430mm(H).	P-603
Mobi-Oil. 3-phase/0.75kW/440V/50Hz. Start/stop (no Cable). All filters included. 4 Heavy Duty Castors with Brakes. 550mm(W)x780mm(D)x1430mm(H).	P-604
Flexi Oil Mist Extraction Arm 2m. Diameter 160mm with turning flange and damper.	P-606
Flexi Oil Mist Extraction Arm 3m. Diameter 160mm with turning flange and damper.	P-607
Replacement HEPA Filter H13 9m².	P-596
Replacement Cassette Filter. Nailed Glass-fiber with Aluminum Separators (4.5+4.5m ²).	P-600