

ORIGINAL[®] Plymoth



Product Catalogue 2024-10-01

J. Plymoth AB, Trarydsallén 4E, 287 72 TRARYD, Sweden. Tel. +46 (0) 40 70015
E-Mail: info@plymoth.com, www.plymoth.com

Product Catalogue

J. Plymoth AB, Trarydsallén 4E, 287 72 TRARYD, Sweden. Tel. +46 (0) 40 70015


1. EXTRACTION ARMS AND EXTRACTION TABLES. DUST, WELDING/SOLDERING-FUME AND GASES.	4
1.1 INSIDE SUPPORT. Flexa Extraction Arms dia. 75/100mm. Length 1m-1.6m. Models for Wall/Ceiling and Table mounting.	4
1.2 INSIDE SUPPORT. Flexi Extraction Arms and Extraction-Cranes. D.160/200mm. 1.5-9m	6
1.3 INSIDE SUPPORT. Flexi Extraction Arms with Turning Flange. Dia.160/200mm. Models for Hanging/Ceiling mounting, 1.5m-5m and for Standing mounting 1,5m-3m.	11
1.4 OUTSIDE SUPPORT. Chemikus Extraction Arms dia. 75/100mm. Length 1m-1.6m. Models for Wall/Ceiling and Table mounting.	13
1.5 OUTSIDE SUPPORT. Super-Max Extraction Arms and Cranes. Dia.100/125/160/200mm. 1.5m-8m.	15
1.6 OUTSIDE SUPPORT. Super-Max Extraction Arms with Turning Flange. D. 75/100/125/160/200mm. Wall-, Ceiling- and Standing mounting.	22
1.7 OUTSIDE SUPPORT. High Vacuum Extraction Arms and Cranes. Dia. 63/75mm. Length 1.5m-8m.	27
1.8 Extraction-Tables WITHOUT Fan and Filter.	30
1.9 Mounting Stanchions and Accessories for all Extraction Arms	32
1.10 "Herkules" Extension Booms for Extraction Cranes. Length 0.5m-4m.	34
2. FANS AND ELECTRIC ACCESSORIES.	36
2.1 Fans and Fan-Brackets for Extraction Arms and Extraction Cranes.	36
2.2 Central Fans.	38
2.3 Mobile Fans.	39
2.4 Electronic Accessories for Fans, Extractor Arms and Extractor-Cranes.	40
3. EXTRACTOR FILTERS. PORTABLE/MOBILE/STATIONARY. DUST, WELDING/SOLDERING, FUME AND GASES.	41
3.1 Portable High Vacuum Extractor Filters for Welding/Soldering Fume	41
3.2 Mobile- Extractor Filters. Welding/Soldering Fume and Light Dust.	42
3.3 Wall-Filters for Light Welding/Soldering, Fume and Light Dust.	47
3.4 Stationary and Central Extractor Filters. Welding/Soldering Fume and Light Dust.	50
3.5 Extractor Filters for Gases. Mobile, Wallmounted and Stationary. Active Carbon 15Ltr/7kg or 30Ltr/15kg.	53
4. FILTER-TABLES. DUST, WELDING/SOLDERING, FUME AND GASES. SITTING (LOW) OR STANDING (HIGH) WORK POSITION.	57
4.1 Filter-Tables/Low. F9 or HEPA H13/W3 Filter. Sitting(Low) Work Position. Light Dust and Light Welding/Soldering Fume.	57
4.2 Filter-Tables/High. F9 or HEPA H13/W3 Filter. Standing (High) Work Position. Light Dust and Light Welding/Soldering Fume.	60
4.3 Filter-Tables for Gases/Odours. Active Carbon Filter Cartridge 15Ltr or 30Ltr. Sitting/Low or Standing/High Work Position.	63
4.4 Filter-Tables (ECO) with Jet-Pulse Cleaning. Sitting(Low) or Standing(High)Work Position. Light Dust and light Welding/Soldering Fume.	65
5. OIL/COOLANT-MIST EXTRACTOR-FILTERS. MOBILE, MACHINE MOUNTED AND STATIONARY.	68
5.1 Mobi-Oil. Mobile Oil/Coolant-Mist Extractor-Filters.	68
5.2 FLX. Machine mounted Oil/Coolant-Mist Extractor-Filters. 600m3/h and 1100m3/h.	69
5.3 NX Stationary Oil/Coolant-Mist Extractor-Filters. Models 400m3/h-8000m3/h. Machine, Wall or Central mounting.	70
6. LABORATORY. DUST, FUME AND GASES. EXTRACTION-ARMS, EXTRACTOR-FILTERS AND FILTER-TABLES.	74
6.1 INSIDE SUPPORT. Flexa Extraction-Arms d. 75/100mm. Length 1m/1.3m/1.6m. Wall/Ceiling and Table mounting.	74
6.2 OUTSIDE SUPPORT. Chemikus Extraction-Arms d. 75/100mm. Length 1m/1.3m/1.6m. Wall/Ceiling and Table mounting.	76
6.3 Extractor-Filters for Dia. 75/100mm Extration-Arms.	78
6.4 Filter-Tables. Dust, Fume and Gases. Sitting(Low) or Standing(High) Work Position.	80

7. CHEMISTRY, PHARMA, FOOD AND LABORATORY.	
ATEX- AND STAINLESS STEEL EXTRACTION-ARMS. FILTER-TABLES.	82
7.1 OUTSIDE SUPPORT. ATEX Super-PM Extraction- Arms. Electrogalvanized with Hood/Handle of Stainless Steel. Dia. 110/160mm. Length 1.5m-4m. ATEX:EX II2D/G	82
7.2 OUTSIDE SUPPORT. ATEX Super-M Extraction Arms. All Parts of Mirror polished, Acidproof Stainless Steel. Dia. 110/160mm. Length 1.5m-4m. ATEX: EX II 2D/G.	87
7.3 OUTSIDE SUPPORT. Chemikus-PM Extraction Arms. Electrogalvanized with Hood/Handle of Stainless Steel. Dia. 75/100mm. Length 1m-1.6m.	92
7.4. OUTSIDE SUPPORT. Super-P Extraction- Arms. All Parts Powder coated. Diameter 110/160mm. Length 1.5-4m.	95
7.5 OUTSIDE SUPPORT. Super-PM Extraction Arms. Hood and Handle of Stainless Steel. All other Parts Powder Coated. Dia. 110/160mm. Length 1.5m-4m.	99
7.7 Extraction-Tables and Filter-Tables for Dust, Fume and Gases.	103
8. DENTIST MOBILE EXTRACTOR-FILTERS.	106
8.1 Denta-Flex 400. Extractor-Filter with d.100mm/1.3m Extraction-Arm.	106
9. VIRUS/BACTERIA AIR PURIFIERS FOR COFFE-, MEETING-, OFFICE AND WAITING ROOMS.	107
9.1 VBF-OFFICE. HEPA H14 Virus/Bacteria Airpurifier. Traditional Model.	107
9.2 Fika-Flex 500. "Clean-Air Shower". Immediately 99.995% Clean Air "Where People meet".	109
10. EXHAUST-GAS REELS, HOSES, NOZZLES, FANS AND HORIZONTAL SUSPENSION ARMS.	110
10.1 Exhaust-Gas Reels. Drum width 475/650/1000/1250mm. Without Hose.	110
10.2 Wall bracket for 1 or 2 Exhaustgas Hoses Dia. 75/100/125/150mm. Without Hose.	111
10.3 EPDM Rubber Exhaust-Gas Hose D.100/125/150mm. Length 7.5m or 10m.	112
10.4 Nozzles for Dia. 100/125/150mm Hose. Nozzleopening Dia 150mm.	113
10.5 Fans for Reels and Wall brackets.	114
10.6 Horizontal Suspension Arms 2-8m for Reels and Wall brackets. Not for Lifting.	115
10.7 Hose Sets for Horizontal Suspension Arms.	117
11. HORIZONTAL SUSPENSION ARMS. 0.5M-8M.	119
11.1 SINGLE ARM. Horizontal Suspension Arms. Not for Lifting!	119
11.2 DOUBLE ARM. Horizontal Suspension Arms. Not for Lifting!	121
11.3 Hose Sets for Horizontal Suspension Arms. Dia. 125/160/200mm.	126
11.4 C-Profiles and Suspension Trolleys for Horizontal Suspension Arms.	128

Product Catalogue 2023-07-01



Art. Nr.

1. EXTRACTION ARMS AND EXTRACTION TABLES. DUST, WELDING/SOLDERING-FUME AND GASES.

1.1 INSIDE SUPPORT. Flexa Extraction Arms dia. 75/100mm. Length 1m-1.6m. Models for Wall/Ceiling and Table mounting.			
P-646	Flexa wall/Ceiling Extractor arm Ø 75/ 1m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-647	Flexa wall/Ceiling Extractor arm Ø 75/ 1,3m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-648	Flexa wall/Ceiling Extractor arm Ø 75/ 1,6m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-652	Flexa wall/Ceiling Extractor arm Ø 100/ 1m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-653	Flexa wall/Ceiling Extractor arm Ø 100/ 1,3m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-654	Flexa wall/Ceiling Extractor arm Ø 100/ 1,6m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		







Product Catalogue 2023-07-01

Art. Nr.

P-649	Flexa Table Extractor arm Ø 75/ 1m Incl. table bracket with turning flange, hose and hood. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-650	Flexa Table Extractor arm Ø 75/ 1,3m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-651	Flexa Table Extractor arm Ø 75/ 1,6m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-656	Flexa Table Extractor arm Ø 100/ 1m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-657	Flexa Table Extractor arm Ø 100/ 1,3m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-658	Flexa Table Extractor arm Ø 100/ 1,6m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		



Product Catalogue 2023-07-01

Art. Nr.

1.2 INSIDE SUPPORT. Flexi Extraction Arms and Extraction-Cranes.D.160/200mm.1.5-9m			
P-006	Flexi Minior Extractor-Arm d. 160mm/1.5m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains it's position. Suitable for schools, small working booths and areas with low ceiling. Prepared for Lamp cartridge in the hood.		 d.160mm
P-007	Flexi Major Extractor-Arm d. 160mm/2m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains it's position		d.160mm
P-008	Flexi Major Extractor-Arm d. 160mm/3m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains it's position.		
P-009	Flexi Horizontal Extractor Arm d. 160mm/4m. Incl. wall bracket, hose and hood with damper. Inside horizontal arm (1m) and inside parallelogram arm (3m). Incredibly easy to move and retains its position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.		d.160mm 
P-010	Flexi Horizontal Extractor Arm d. 160mm/5m. Incl. wall bracket, hose and hood with damper. Inside horizontal arm (2m) and inside parallelogram arm (3m). Incredibly easy to move and retains its position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.		 Flexi Horizontal 4-5m
P-104	Flexi Extractor-Crane d. 160mm/4m (2+2m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		d.160mm 
P-034	Flexi Extractor-Crane d. 160mm/5m (2+3m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		 Flexi Extractor-Crane 4-9m





Product Catalogue 2023-07-01

Art. Nr.

P-036	Flexi Extractor-Crane d. 160mm/6m (2+4m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		 Flexi Extractor-Crane 4-9m
P-039	Flexi Extractor-Crane d. 160mm/ 7m (2+5m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-035	Flexi Extractor-Crane d. 160mm/5m (3+2m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-037	Flexi Extractor-Crane d. 160mm/6m (3+3m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		d.160mm
P-040	Flexi Extractor-Crane d. 160mm/7m (3+4m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		 Flexi Extractor-Crane 4-9m
P-042	Flexi Extractor-Crane d. 160mm/8m (3+5m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-038	Flexi Extractor-Crane d. 160mm/6m (4+2m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-041	Flexi Extractor-Crane d. 160mm/7m (4+3m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		


Product Catalogue 2023-07-01

Art. Nr.

P-043	Flexi Extractor-Crane d. 160mm/8m (4+4m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		d.160mm 
P-044	Flexi Extractor-Crane d. 160mm/9m (4+5m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		Flexi Extractor-Crane 4-9m
P-142	Flexi Minior Extractor-Arm d. 200mm/1.5m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains its position. Suitable for schools, small working booths and areas with low ceiling. Prepared for Lamp cartridge in the hood.		d.200mm  Flexi Minior 1.5m
P-143	Flexi Major Extractor-Arm d. 200mm/2m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains its position. Prepared for Lamp cartridge in the hood.		d.200mm 
P-144	Flexi Major Extractor-Arm d. 200mm/3m. Incl. Wall bracket, hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and retains its position. Prepared for Lamp cartridge in the hood.		Flexi Major 2-3m
P-145	Flexi Horizontal Extractor Arm d. 200mm/4m. Incl. Wall bracket, hose and hood with damper. Inside horizontal arm (1m) and inside parallelogram arm (3m). Incredibly easy to move and retains its position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.		d.200mm 
P-146	Flexi Horizontal Extractor Arm d. 200mm/5m. Incl. Wall bracket, hose and hood with damper. Inside horizontal arm (2m) and inside parallelogram arm (3m). Incredibly easy to move and retains its position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.		Flexi Horizontal 4-5m


Product Catalogue 2023-07-01

Art. Nr.

P-105	Flexi Extractor-Crane d. 200mm/4m (2+2m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		<p>d.200mm</p>  <p>Flexi Extractor-Crane 4-9m</p>
P-162	Flexi Extractor-Crane d. 200mm/5m (2+3m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-173	Flexi Extractor-Crane d. 200mm/6m (2+4m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-175	Flexi Extractor-Crane d. 200mm/7m (2+5m). Incl. Wall bracket, horizontal support arm (2m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-172	Flexi Extractor-Crane d. 200mm/5m (3+2m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-163	Flexi Extractor-Crane d. 200mm/6m (3+3m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-164	Flexi Extractor-Crane d. 200mm/7m (3+4m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-177	Flexi Extractor-Crane d. 200mm/8m (3+5m). Incl. Wall bracket, horizontal support arm (3m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		




Product Catalogue 2023-07-01

Art. Nr.

P-174	Flexi Extractor-Crane d. 200mm/6m (4+2m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (2m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-176	Flexi Extractor-Crane d. 200mm/7m (4+3m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (3m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		<p>d.200mm</p>  <p>Flexi Extractor-Crane 4-9m</p>
P-165	Flexi Extractor-Crane d. 200mm/8m (4+4m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (4m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		
P-166	Flexi Extractor-Crane d. 200mm/9m (4+5m). Incl. Wall bracket, horizontal support arm (4m) with ball-bearings and disc brake, extractor arm (5m), hose and hood with damper. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the horizontal support arm.		






Product Catalogue 2023-07-01

Art. Nr.

<p>1.3 INSIDE SUPPORT. Flexi Extraction Arms with Turning Flange. Dia.160/200mm. Models for Hanging/Ceiling mounting, 1.5m-5m and for Standing mounting 1,5m-3m.</p>			
P-051	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d. 160mm/1.5m.Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-052	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>d.160mm</p>  <p>Flexi FLT Ceiling 1.5-3m</p>
P-053	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-054	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d.160mm/4m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside horizontal arm (1m) and inside parallelogram arm (3m). Incredibly easy to move and stays in position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.</p>		<p>d.160mm</p>  <p>Flexi FLT Ceiling 4-5m</p>
P-055	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d.160mm/5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside horizontal arm (2m) and inside parallelogram arm (3m). Incredibly easy to move and stays in position. Suitable for car repair shops and areas with low ceiling. Prepared for Lamp cartridge in the hood.</p>		
P-056	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d. 200mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		 <p>Flexi FLT Ceiling 1.5-3m</p>
P-057	<p>Flexi FLT Ceiling-Extractor Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>d.200mm</p>



Product Catalogue 2023-07-01

Art. Nr.

P-058	Flexi FLT Ceiling-Extractor Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 Flexi FLT Ceiling 1.5-3m
P-059	Flexi FLT Ceiling-Extractor Arm with turning flange d. 200mm/4m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside horizontal arm (1m) and inside parallelogram (3m). Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.200mm 
P-087	Flexi FLT Ceiling-Extractor Arm with turning flange d. 200mm/5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside horizontal arm (2m) and inside parallelogram (3m). Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 Flexi FLT Ceiling 4-5m
P-069	Flexi FLB Table Extractor Arm with turning flange d. 160mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-168	Flexi FLB Table Extractor Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.160mm  Flexi FLB Table 1.5-3m
P-169	Flexi FLB Table Extractor Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-167	Flexi FLB Table Extractor Arm with turning flange d. 200mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.200mm
P-170	Flexi FLB Table Extractor Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 Flexi FLB Table 1.5-3m
P-171	Flexi FLB Table Extractor Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		


Product Catalogue 2023-07-01

Art. Nr.

1.4 OUTSIDE SUPPORT. Chemikus Extraction Arms dia. 75/100mm. Length 1m- 1.6m. Models for Wall/Ceiling and Table mounting.				
P-660	Chemikus wall/ceilings Extractor arm Ø 75/ 1m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-661	Chemikus wall/ceilings Extractor arm Ø 75/ 1,3m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-662	Chemikus wall/ceilings Extractor arm Ø 75/ 1,6m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-666	Chemikus wall/ceilings Extractor arm Ø 100/ 1m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-667	Chemikus wall/ceilings Extractor arm Ø100/ 1,3m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-668	Chemikus wall/ceilings Extractor arm Ø 100/ 1,6m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.			
P-663	Chemikus Table Extractor arm Ø 75/1m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.			


Product Catalogue 2023-07-01

Art. Nr.

P-664	Chemikus Table Extractor arm Ø 75/1,3m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-665	Chemikus Table Extractor arm Ø 75/1,6m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-669	Chemikus Table Extractor arm Ø 100/1m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-670	Chemikus Table Extractor arm Ø 100/1,3m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-671	Chemikus Table Extractor arm Ø 100/1,6m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		




Product Catalogue 2023-07-01

Art. Nr.

1.5 OUTSIDE SUPPORT. Super-Max Extraction Arms and Cranes. Dia.100/125/160/200mm. 1.5m-8m.			
P-068	Super-Max Extractor Arm d. 100mm/1.5m (0.25+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 <p>d.100mm Super-Max 1.5-4m</p>
P-123	Super-Max Extractor Arm d. 100mm/1.5m (0.5+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-070	Super-Max Extractor Arm d. 100mm/2m (0.25+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-124	Super-Max Extractor Arm d. 100mm/2m (0.5+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-072	Super-Max Extractor Arm d. 100mm/3m (0.5+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-073	Super-Max Extractor Arm d. 100mm/4m (0.5+0.6+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-275	Super-Max Extractor-Crane d. 100mm/4m (2+2m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (2m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		
P-276	Super-Max Extractor-Crane d. 100mm/5m (2+3m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		





Product Catalogue 2023-07-01

Art. Nr.

P-277	Super-Max Extractor-Crane d. 100mm/6m (3+3m) Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		d.100mm 
P-278	Super-Max Extractor-Crane d. 100mm/7m (4+3m) Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		 Super-Max Extractor-Crane 4-8m
P-279	Super-Max Extractor-Crane d. 100mm/8m (5+3m) Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		
P-075	Super-Max Extractor Arm d. 125mm/1.5m (0.25+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.125mm
P-076	Super-Max Extractor Arm d. 125mm/1.5m (0.5+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 Super-Max 1.5-4m
P-077	Super-Max Extractor Arm d. 125mm/2m (0.25+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-078	Super-Max Extractor Arm d. 125mm/2m (0.5+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		



Product Catalogue 2023-07-01

Art. Nr.

P-079	Super-Max Extractor Arm d. 125mm/3m (0.5+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.125mm 
P-080	Super-Max Extractor Arm d. 125mm/4m (0.5+0.6+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Super-Max 1.5-4m 
P-280	Super-Max Extractor-Crane d. 125mm/4m (2+2m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (2m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		
P-281	Super-Max Extractor-Crane d. 125mm/5m (2+3m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		d.125mm 
P-282	Super-Max Extractor-Crane d. 125mm/6m (3+3m) Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		Super-Max Extractor-Crane 4-8m 
P-283	Super-Max Extractor-Crane d. 125mm/7m (4+3m) Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		
P-284	Super-Max Extractor-Crane d. 125mm/8m (5+3m) Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		



Product Catalogue 2023-07-01

Art. Nr.

P-112	Super-Max Extractor Arm d. 160mm/1.5m (0.25+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-113	Super-Max Extractor Arm d. 160mm/1.5m (0.5+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-114	Super-Max Extractor Arm d. 160mm/2m (0.25+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.160mm  Super-Max 1.5-4m
P-115	Super-Max Extractor Arm d. 160mm/2m (0.5+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-117	Super-Max Extractor Arm d. 160mm/3m (0.5+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-121	Super-Max Extractor Arm d. 160mm/4m (0.5+0.6+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-125	Super-Max Extractor-Crane d. 160mm/4m (2+2m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (2m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		 Super-Max Extractor-Crane 4-8m
P-126	Super-Max Extractor-Crane d. 160mm/5m (2+3m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		d.160mm



Product Catalogue 2023-07-01

Art. Nr.

P-127	Super-Max Extractor-Crane d. 160mm/6m (3+3m) Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		d.160mm
P-128	Super-Max Extractor-Crane d. 160mm/7m (4+3m) Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		 <p>Super-Max Extractor-Crane 4-8m</p>
P-129	Super-Max Extractor-Crane d. 160mm/8m (5+3m) Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		
P-292	Super-Max Extractor Arm d. 200mm/1.5m (0.25+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-293	Super-Max Extractor Arm d. 200mm/1.5m (0.5+1.5m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-294	Super-Max Extractor Arm d. 200mm/2m (0.25+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.200mm  <p>Super-Max 1.5-4m</p>
P-295	Super-Max Extractor Arm d. 200mm/2m (0.5+2m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		


Product Catalogue 2023-07-01

Art. Nr.

P-296	<p>Super-Max Extractor Arm d. 200mm/3m (0.5+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		 <p>Super-Max 1.5-4m</p>
P-297	<p>Super-Max Extractor Arm d. 200mm/4m (0.5+0.6+3m) Incl. Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>d.200mm</p>
P-286	<p>Super-Max Extractor-Crane d. 200mm/4m (2+2m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (2m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm</p>		
P-287	<p>Super-Max Extractor-Crane d. 200mm/5m (2+3m) Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.</p>		<p>d.200mm</p>
P-288	<p>Super-Max Extractor-Crane d. 200mm/6m (3+3m) Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.</p>		 <p>Super-Max Extractor-Crane 4-8m</p>
P-289	<p>Super-Max Extractor-Crane d. 200mm/7m (4+3m) Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.</p>		



Product Catalogue 2023-07-01

Art. Nr.

P-290	Super-Max Extractor-Crane d. 200mm/8m (5+3m) Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extraction arm (3m) with hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile (30/30mm) under the first horizontal support arm.		 <p>Super-Max Extractor-Crane 4-8m</p>
-------	--	--	--



Product Catalogue 2023-07-01

Art. Nr.

<p>1.6 OUTSIDE SUPPORT.Super-Max Extraction Arms with Turning Flange. D. 75/100/125/160/200mm. Wall-, Ceiling- and Standing mounting.</p>			
P-407	<p>Super-Max SMSV Extractor Arm d.75mm/1,5m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>d.75mm</p>  <p>Super-Max SMSV 1.5-4m with Turning Flange Wallbracket</p>
P-408	<p>Super-Max SMSV Extractor Arm d.75mm/2m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-409	<p>Super-Max SMSV Extractor Arm d.75mm/3m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-410	<p>Super-Max SMSV Extractor Arm d.75mm/4m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-411	<p>Super-Max SMSV Extractor Arm d.100mm/1,5m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>d.100mm</p>  <p>Super-Max SMSV 1.5-4m with Turning Flange Wallbracket</p>
P-412	<p>Super-Max SMSV Extractor Arm d.100mm/2m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-413	<p>Super-Max SMSV Extractor Arm d.100mm/3m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		



Product Catalogue 2023-07-01

Art. Nr.

P-414	Super-Max SMSV Extractor Arm d.100mm/4m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-415	Super-Max SMSV Extractor Arm d.125mm/1,5m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 <p>d.125mm</p> <p>Super-Max SMSV 1.5-4m with Turning Flange Wallbracket</p>
P-416	Super-Max SMSV Extractor Arm d.125mm/2m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-417	Super-Max SMSV Extractor Arm d.125mm/3m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-418	Super-Max SMSV Extractor Arm d.125mm/4m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-419	Super-Max SMSV Extractor Arm d.160mm/1.5m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		 <p>Super-Max SMSV 1.5-4m with Turning Flange Wallbracket</p> <p>d.160mm</p>
P-420	Super-Max SMSV Extractor Arm d.160mm/2m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-421	Super-Max SMSV Extractor Arm d.160mm/3m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		



Product Catalogue 2023-07-01

Art. Nr.

P-422	Super-Max SMSV Extractor Arm d.160mm/4m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-423	Super-Max SMSV Extractor Arm d.200mm/1.5m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-424	Super-Max SMSV Extractor Arm d.200mm/2m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.200mm 
P-425	Super-Max SMSV Extractor Arm d.200mm/3m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Super-Max SMSV 1.5-4m with Turning Flange Wallbracket
P-426	Super-Max SMSV Extractor Arm d.200mm/4m with Turning Flange Wall bracket. Incl. turning flange Wall bracket, hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-130	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.160mm/1.5m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-135	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.160mm/2m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Super-Max SMT Ceiling 1.5-4m d.160mm
P-136	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.160mm/3m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		


Product Catalogue 2023-07-01

Art. Nr.

P-152	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.160mm/4m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-223	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.200mm/1.5m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-224	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.200mm/2m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		d.200mm 
P-225	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.200mm/3m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Super-Max SMT Ceiling 1.5-4m
P-231	Super-Max SMT Ceiling-Extractor Arm with Turning Flange d.200mm/4m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-232	Super-Max SMB Table-Extractor Arm with Turning Flange d. 160mm/1.5m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-233	Super-Max SMB Table-Extractor Arm with Turning Flange d. 160mm/2m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Super-Max SMB Table 1.5-4m d.160mm
P-110	Super-Max SMB Table-Extractor Arm with Turning Flange d. 160mm/3m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		


Product Catalogue 2023-07-01

Art. Nr.

P-111	<p>Super-Max SMB Table-Extractor Arm with Turning Flange d. 160mm/4m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		 Super-Max SMB Table 1.5-4m
P-237	<p>Super-Max SMB Table-Extractor Arm with Turning Flange d. 200mm/1.5m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-238	<p>Super-Max SMB Table-Extractor Arm with Turning Flange d. 200mm/2m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-119	<p>Super-Max SMB Table-Extractor Arm with Turning Flange d. 200mm/3m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
P-120	<p>Super-Max SMB Table-Extractor Arm with Turning Flange d. 200mm/4m Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		d.200mm


Product Catalogue 2023-07-01

Art. Nr.

1.7 OUTSIDE SUPPORT. High Vacuum Extraction Arms and Cranes. Dia. 63/75mm. Length 1.5m-8m.			
P-060	Super-Vac High Vacuum Extractor Arm d. 63mm/1.5m (0.25+1.5m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		d.63mm  Super-Vac 1.5-4m
P-061	Super-Vac High Vacuum Extractor Arm d. 63mm/2m (0.25+2m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-062	Super-Vac High Vacuum Extractor Arm d. 63mm/3m (0.25+3m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-063	Super-Vac High Vacuum Extractor Arm d. 63mm/4m (0.5+0.6+3m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-090	Super-Vac High Vacuum Extractor-Crane d. 63mm/4m (2+2m). Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extractor arm (2m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		d.63mm Super-Vac Extractor-Crane 4-8m
P-091	Super-Vac High Vacuum Extractor-Crane d. 63mm/5m (2+3m). Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		
P-092	Super-Vac High Vacuum Extractor-Crane d. 63mm/6m (3+3m). Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		
P-093	Super-Vac High Vacuum Extractor-Crane d. 63mm/7m (4+3m). Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		
P-093	Super-Vac High Vacuum Extractor-Crane d. 63mm/7m (4+3m). Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		

Product Catalogue 2023-07-01

Art. Nr.

P-094	Super-Vac High Vacuum Extractor-Crane d. 63mm/8m (5+3m). Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		d.63mm Super-Vac Extractor-Crane 4-8m
P-064	Super-Vac High Vacuum Extractor Arm d. 75mm/1.5m (0.25+1.5m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-065	Super-Vac High Vacuum Extractor Arm d. 75mm/2m (0.25+2m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		d.75mm 
P-066	Super-Vac High Vacuum Extractor Arm d. 75mm/3m (0.25+3m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		Super-Vac 1.5-4m
P-067	Super-Vac High Vacuum Extractor Arm d. 75mm/4m (0.5+0.6+3m). Incl. Wall bracket, high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-095	Super-Vac High Vacuum Extractor-Crane d. 75mm/4m (2+2m). Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extractor arm (2m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		
P-096	Super-Vac High Vacuum Extractor-Crane d. 75mm/5m (2+3m). Incl. Wall bracket, two horizontal support arms (2m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		d.75mm Super-Vac Extractor-Crane 4-8m
P-097	Super-Vac High Vacuum Extractor-Crane d. 75mm/6m (3+3m). Incl. Wall bracket, two horizontal support arms (3m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		





Product Catalogue 2023-07-01

Art. Nr.

P-098	Super-Vac High Vacuum Extractor-Crane d. 75mm/7m (4+3m). Incl. Wall bracket, two horizontal support arms (4m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		d.75mm Super-Vac Extractor-Crane 4-8m
P-099	Super-Vac High Vacuum Extractor-Crane d. 75mm/8m (5+3m). Incl. Wall bracket, two horizontal support arms (5m) with ball-bearings and disc brakes, extractor arm (3m) with high vacuum hose and hood with damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood and C-profile under the first horizontal support arm.		




Product Catalogue 2023-07-01

Art. Nr.

1.8 Extraction-Tables WITHOUT Fan and Filter.			
P-774	Super-Mesa 1m Backdraft Table prepared for Extraction Arm. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1mx1m. Connection to extraction diameter 199mm outside.		
P-775	Super-Mesa 1.4m Backdraft Table prepared for Extraction Arm. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1.4mx1m. Connection to extraction 2x diameter 199mm outside.		
P-776	Maxi-Mesa 1m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with a table top of 75mm wide u-formed iron bars and 15mm slots in between , 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1mx1m. Connection for extraction diameter 199mm outside.		
P-777	Maxi-Mesa 1.4m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with a table top of 75mm wide u-formed iron bars and 15mm slots in between , 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1.4mx1m. Connection for extraction 2x diameter 199mm outside.		




Product Catalogue 2023-07-01

Art. Nr.

P-782	<p>Maxi-Mesa 1m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with table top of 40x5mm vertical flat bar-irons with 50mm in between, 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1mx1m. Connection for extraction diameter 199mm outside.</p>		
P-783	<p>Maxi-Mesa 1.4m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with table top of 40x5mm flat bar-irons with 50mm in between, 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Adjustable height 800-950mm. Measure 1.4mx1m. Connection for extraction 2x diameter 199mm outside.</p>		
P-778	<p>Spark Trap for Super-Mesa/Maxi-Mesa 1m. 2 pcs.</p>		
P-779	<p>Spark Trap for Super-Mesa/Maxi-Mesa 1.4m. 2 pcs.</p>		
P-069	<p>Flexi FLB 1.5m Extraction Arm. Diameter 160mm.</p>		
P-168	<p>Flexi FLB 2m Extraction Arm. Diameter 160mm.</p>		 <p>Flexi FLB Table 1.5-3m</p>
P-169	<p>Flexi FLB 3m Extraction Arm. Diameter 160mm.</p>		




Product Catalogue 2023-07-01

Art. Nr.

1.9 Mounting Stanchions and Accessories for all Extraction Arms			
P-427	Floor/Ceiling Stanchion 0.5m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		 <p>Flexi Floor/Ceiling Stanchion</p>
P-428	Floor/Ceiling Stanchion 0.75m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-021	Floor/Ceiling Stanchion 1m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-429	Floor/Ceiling Stanchion 1.25m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-430	Floor/Ceiling Stanchion 1.5m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-431	Floor/Ceiling Stanchion 1.75m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-022	Floor/Ceiling Stanchion 2m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-432	Floor/Ceiling Stanchion 2.25m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-433	Floor/Ceiling Stanchion 2.5m for Flexi Extraction Arms 1.5-5m and Super-Max SMSV.		
P-434	Floor/Ceiling Stanchion 0.5m for Super-Max 1,5-4m.		 <p>Pro-Flex/Super-Max Floor/Ceiling Stanchion</p>
P-435	Floor/Ceiling Stanchion 0.75m for Super-Max 1,5-4m.		
P-083	Floor/Ceiling Stanchion 1m for Super-Max 1,5-4m.		
P-436	Floor/Ceiling Stanchion 1.25m for Super-Max 1,5-4m.		
P-437	Floor/Ceiling Stanchion 1.5m for Super-Max 1,5-4m.		
P-438	Floor/Ceiling Stanchion 1.75m for Super-Max 1,5-4m.		
P-084	Floor/Ceiling Stanchion 2m for Super-Max 1,5-4m.		
P-439	Floor/Ceiling Stanchion 2.25m for Super-Max 1,5-4m.		
P-440	Floor/Ceiling Stanchion 2.5m for Super-Max 1,5-4m.		
P-050	Suspension Shackle with turning joint. Max. hanging weight 60 kg. Not for lifting. Fits the first horizontal arm of Extractor Cranes and Support Arms (not Herkules). Incl. suspension shackle with turning joint, carbine hook and M10/90mm bolt with nut.		


Product Catalogue 2023-07-01

Art. Nr.

P-027	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 1.3m. Incl. C-profile 30/30/10/2mm L. 820mm with 3 M10/90mm bolts and nuts.		
P-028	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 2.3m. Incl. C-profile 30/30/10/2mm L. 1870mm with 6 M10/90mm bolts and nuts.		
P-029	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 3m. Incl. C-profile 30/30/10/2mm L. 2570mm with 8 M10/90mm bolts and nuts.		
P-023	Suspension Trolley with 4 Ball Bearing Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 60 kg weight (not for lifting). Incl. trolley with 4 ball bearing wheels.		
P-024	Suspension Trolley with plastic Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 10 kg weight (not for lifting). Incl. trolley with 2 plastic wheels, S-hook and a sling.		

Product Catalogue 2023-07-01

Art. Nr.

<p>1.10 “Herkules” Extension Booms for Extraction Cranes. Length 0.5m-4m.</p>			
P-156	<p>Herkules Suspension Arm 0.5m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 0.5m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".</p>		 <p>Herkules 0.5-4 m</p>
P-193	<p>Herkules Suspension Arm 1m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 1m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".</p>		
P-194	<p>Herkules Suspension Arm 2m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 2m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".</p>		
P-195	<p>Herkules Suspension Arm 3m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 3m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".</p>		
P-190	<p>Herkules Suspension Arm 4m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 4m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".</p>		

Product Catalogue 2023-07-01

Art. Nr.


P-472	Hose Set d. 125mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.125mm hose, 2 hose clamps, 3 hose bands and one d.125mm hose connection.		
P-449	Hose Set d. 160mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.160mm hose, 2 hose clamps, 3 hose bands and one d.160mm hose connection.		
P-473	Hose Set d. 200mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.200mm hose, 2 hose clamps, 3 hose bands and one d.200mm hose connection.		
P-474	Hose Set d. 125mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.125mm hose, 2 hose clamps, 4 hose bands and one d.125mm hose connection.		

Product Catalogue 2023-07-01

Art. Nr.





2. FANS AND ELECTRIC ACCESSORIES.

2.1 Fans and Fan-Brackets for Extraction Arms and Extraction Cranes.

P-011	P-Max Fan 0.37 kW/3-Phase/1300m3 freeblowing/ 230V/400V/50Hz/440V/60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes and Exhaustgas- Hose reels.		<p>P-Max fans</p> 
P-012	P-Max Fan 0.75 kW/3-Phase/2100m3 freeblowing/ 230V/400V/50Hz/440V/60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas- Hose reels.		
P-013	P-Max Fan TURBO 0.75 kW/3-Phase/2100m3 230V/400V/50Hz/440V/60Hz. <i>Must not be run freeblowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.		
P-032	P-Max Fan 1.1 kW/3-Phase/2100m3 freeblowing/ 230V/400V/50Hz/440V/60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.		
P-122	V-Max Fan without Support Bracket and Inlet/ 1.1 kW/3-Phase/3000m3 freeblowing /230V/400V/50Hz/440V/60Hz. Incl. fan case, motor and outlet 145/220mm. For mounting directly on the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhausthose-Wall brackets. For mounting on Fan Brackets for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.		
P-015	P-Max Fan 0.75 kW/1-Phase TURBO/2100m3/ 220V/50Hz. <i>Must not be run freeblowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-, Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.		

Product Catalogue 2023-07-01


Art. Nr.

P-088	Fan Bracket and Inlet d. 125mm for Super-Max Extractor Arms with d. 125mm or thinner hose. Can also be used for Super-Max and Pro-Flex Extractor-Cranes with d. 125mm or thinner hose.		<p>Fan brackets 2pcs.</p> 
P-016	Fan Bracket and Inlet d. 160mm for Super-Max Extractor Arms with d. 160mm hose. Can be used for Super-Max and Pro-Flex Extractor-Cranes (However Fan Bracket with Turning Flange for the hose is strongly recommended).		<p>Inlet for Pro-Flex och Super-Max</p> 
P-089	Fan Bracket and Inlet d. 200mm for Super-Max Extractor Arms with d. 200mm hose.		
P-045	Fan Bracket with d. 160mm Turning Flange for Extractor-Cranes. For Flexi-and Super-Max Extractor-Cranes. With the fan bracket the hose will not break at the connection to the fan, when the first horizontal support arm is moved up towards the wall.		<p>d.160/200 mm</p>  <p>Fan bracket for Extractor-Cranes</p>
P-151	Fan Bracket with d. 200mm Turning Flange for Extractor-Cranes. For Flexi-and Super-Max Extractor-Cranes. With the fan bracket the hose will not break at the connection to the fan, when the first horizontal support arm is moved up towards the wall.		
P-030	Turning Flange for d. 160mm Hose for Extractor-Cranes. For Flexi- and Super-Max Extractor-Cranes. To be mounted at the connection between hose and ventilation ducting at the wall in central extraction systems. With the turning flange the hose will not break at the connection at the wall, when the first horizontal support arm is moved up towards the wall.		
P-031	Turning Flange for d. 200mm Hose for Extractor-Cranes. For Flexi- and Super-Max Extractor-Cranes. To be mounted at the connection between hose and ventilation ducting at the wall in central extraction systems. With the turning flange the hose will not break at the connection at the wall, when the first horizontal support arm is moved up towards the wall.		 <p>Turning Flange d. 160/200 mm</p>
P-133	Central Fan V-Max 3000 m3/1.1 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.250mm, outlet 145x220mm and motor 1.1 kW/ 3-Phase/230V/380-420V /50Hz/2.7A/IP55/440V/60Hz.		
P-134	Central Fan V-Max 4600 m3/2.2 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.250mm, outlet 145x220mm and motor 2.2 kW/ 3-Phase/230V/380-420V /50Hz/4.6A/IP55/440V/60Hz.		

Product Catalogue 2023-07-01




Art. Nr.

2.2 Central Fans.

P-131	Central Fan V-Max 1300 m ³ /0.37 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.160mm, outlet d.200mm (inside measure) and motor 0.37 kW/3-Phase/230V/380-420V/50Hz/1A/IP55/ 440V/60Hz.		
P-132	Central Fan V-Max 2100 m³/0.75 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.160mm, outlet d.200mm (inside measure) and motor 0.75 kW/3-Phase/230V/380-420V /50Hz/2A/IP55/ 440V/60Hz.		
P-133	Central Fan V-Max 3000 m³/1.1 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.250mm, outlet 145x220mm and motor 1.1 kW/ 3-Phase/230V/380-420V /50Hz/2.7A/IP55/440V/60Hz.		
P-134	Central Fan V-Max 4600 m³/2.2 kW/3-Phase with support for floor/wall/ceiling mounting. Incl. fan case, inlet d.250mm, outlet 145x220mm and motor 2.2 kW/ 3-Phase/230V/380-420V /50Hz/4.6A/IP55/440V/60Hz		

Product Catalogue 2023-07-01






Art. Nr.

2.3 Mobile Fans.			
P-324	Mobi-Fan 0.75 kW/1-Phase/220V/50Hz. Mobile Fan on wheels with handle, circuit-breaker with motor cut-out, 4m cable with plug, d.159 mm inlet (outside measure) and d.200 mm outlet (inside measure).		
P-402	Mobi-Fan 0.75kW/3-Phase/230V/380-420V/50Hz/440V/60Hz. Mobile Fan on wheels with handle, circuit-breaker with motor cut-out, d.159 mm inlet (outside measure) and d. 200 mm outlet (inside measure). Cable and plug not included.		
P-017	Extension Hose 2m d. 160mm with Magnet Hood. Incl. hood with support and two magnets, 2m d.160mm hose, 2 hose clamps and quick connection which fits the hood of d.125 or 160 mm extractor arms and extractor-cranes.		 Extension Hose with Magnet Hood
P-018	Extension Hose 3m d. 160mm with Magnet Hood. Incl. hood with support and two magnets, 3m d.160mm hose, 2 hose clamps and quick connection which fits the hood of d.125 or 160 mm extractor arms and extractor-cranes.		
P-396	Hose 2m d. 160mm and 2 Hose Clamps. Incl. 2m d. 160mm hose, 2 hose clamps and quick connection which fits the hood of d.125 or 160 mm extractor arms and extractor-cranes (not needed for Mobi-Fan).		 Extension Hose
P-397	Hose 3m d. 160mm and 2 Hose Clamps. Incl. 3m d. 160mm hose, 2 hose clamps and quick connection which fits the hood of d.125 or 160 mm mmextractor arms and extractor-cranes (not needed for Mobi-Fan).		
P-398	Hose 6m d. 160mm and 2 Hose Clamps. Incl. 6m d. 160mm hose, 2 hose clamps and quick connection which fits the hood of d.125 or 160 mm extractor arms and extractor-cranes (not needed for Mobi-Fan).		
P-399	Extension Hose 2m d. 200mm+ 1 Hose Clamp + Flange for d 200 Outlet of Mobi- Fan.		
P-400	Extension Hose 3m d. 200mm+ 1 Hose Clamp + Flange for d 200 Outlet of Mobi- Fan.		
P-401	Reduction D.200/160. Fits into d 200 mm Outlet of the Mobi-Fan.		

Product Catalogue 2023-07-01

Art. Nr.




2.4 Electronic Accessories for Fans, Extractor Arms and Extractor-Cranes.

P-019	Halogen Lamp Cartridge 20 Watt/12V. For d.125/160/200 mm Hoods (Flexi Hoods and Super-Max Hoods)		
P-020	Transformer 220/12V for Halogen Lamp Cartridge above.		
P-109	S-Max. Automatic motorized Damper. Automatic open/close Function of the Damper when welding. Unit with electronics, transformer 220/24/12V, 5 m cable with sensor clamp (double Hall sensors for safe sensing) and motorized damper. 30sec overrun time. Lamp P-019 can be connected.		
P-118	C-Max. Energy saving Control Unit for Central Extraction Fan. Combined with E-Max or S-Max it will start the central fan when welding takes place. Unit with electronics, transformer 220/24/12 V and contactor for up to 4.4 kW (380-420 Volt) fan motor. Must be combined with relevant motor overload protection (not included).		
P-014	E-Max Energy Saver. Automatic Start/Stop of Fan when welding. Unit with electronics, transformer 220/24/12V, contactor and 5 m cable with sensor clamp (double Hall sensors for safe sensing). 30 sec overrun time. Must be combined with relevant motor overload protection (not included). Lamp P-019 can be connected		
P-025	E-Man. 24 Volt Starter of Fan from the Hood. Unit for wall mounting with contactor and transformer 220/24/12V. 5 m cable with start/stop switch for mounting on the Hood. Must be combined with relevant motor overload protection (not included). Lamp P-019 can be connected		

Product Catalogue 2023-07-01






Art. Nr.

3. Extractor Filters. Portable/Mobile/Stationary. Dust, Welding/Soldering, Fume and Gases.

3.1 Portable High Vacuum Extractor Filters for Welding/Soldering Fume			
P-609	Porta-Flex 200 portable welding Fume Filter. 1-Phase/220V/50Hz. Incl. filterbox and handle of powder painted steel sheet, spark trap, filter cartridge, high vacuum fan 1-phase/220V/1kW/50Hz, 4m cable with plug and 2.5m extraction hose. Nozzle has to be ordered separately.		
P-611	Porta-Flex 400 portable welding Fume Filter. 1-Phase/ 220V/50Hz. Incl. filterbox and handle of powder painted steel sheet, spark trap, filter cartridge, 2 high vacuum fans 1-phase/220V/1kW/50Hz, 4m cable with plug and 2.5m extraction hose. Nozzle has to be ordered separately.		
P-613	Porta-Flex 200 Auto portable welding Fume Filter with auto Start/Stop. 1-phase/220V/50Hz. Incl. filterbox and handle of powder painted steel sheet, spark trap, filter cartridge, high vacuum fan with auto start/stop with 4m cable and sensor 1-phase/220V/1kW/50Hz, 4m cable with plug and 2.5m extraction hose. Nozzle has to be ordered separately.		
P-615	Magnet Nozzle 400mm wide.		
P-616	Magnet Nozzle 300mm wide.		
P-617	Magnet Nozzle 200mm wide.		
P-618	Magnet Nozzle 80mm wide with flexible steel hose.		
P-619	Replacement Filter for Porta-Flex 200/400/200Auto.		
P-620	HEPA Filter H13/W3, 12m2 for Porta-Flex 200/400/200Auto.		





Product Catalogue 2023-07-01

Art. Nr.

<h2 style="margin: 0;">3.2 Mobile- Extractor Filters.</h2> <h3 style="margin: 0;">Welding/Soldering Fume and Light Dust.</h3>			
P-001	<p>MF-F9. Mobile Extractor-Filter with F9 Filter Cartridge. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder coated steel sheet with 4 Castors with brakes, F9 filtercartridge (12 m2), 1-phase/1.1 kW/220V/50Hz fan, circuit breaker, motor overload protection and 4m cable with plug. Order Flexi FLB- Extraction Arm separately.</p>		
P-957	<p>MF-HEPA H13/W3 (9m2). Mobile Extractor-Filter with HEPA H13/W3 Filter for <i>Stainless Steel Welding</i>. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder coated steel sheet with 4 Castors with brakes, HEPA H13/W3 filter (9m2) with Prefilter Fleece, over 99.95 % efficiency, 1-phase/1.1kW/220V/50Hz fan, circuit breaker, motor overload protection and 4m cable with plug. Order Flexi FLB- Extraction Arm separately.</p>		
P-791	<p>MF-HEPA (18m2) Mobile Extractor-Filter with F9 Pre-Filter (9m2) and HEPA H13/W3 Filter (9M2) for <i>Stainless Steel Welding</i>. 1-Phase/1.1kW/220V/50Hz. Incl. filter box of powder coated steel sheet with 4 Castors with brakes, F9 pre-filter (9m2) cartridge, HEPA H13/W3 filter (9m2) with over 99.95% efficiency, 1-phase/1.1kW/220V/50Hz fan, circuit breaker with motor overload protection and 4m cable with plug. Order Flexi FLB- Extraxtion Arm separately.</p>		
P-794	<p>MF-HEPA (18m2) Mobile Extractor-Filter with F9 Prefilter (9m2) and HEPA H13/W3 (9M2) Filter for <i>Stainless Steel Welding</i>. 3-Phase/1.1kW 380-420V/50Hz. Incl. filter box of powder coated steel sheet with 4 Castors with brakes, F9 pre-filter (9m2) cartridge, HEPA H13/W3 filter (9m2) with over 99.95% efficiency, 3-phase/1.1kW/380-420V/50Hz fan, circuit breaker with motor overload protection and 4m cable (plug not incl). Order Flexi FLB- Extraction Arm separately.</p>		
P-540	<p>MF-Eco F9 Jet-Pulse. Mobile Extractor-Filter with compressed air cleaning. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder coated steel sheet with 4 wheels with brakes, F9 Filter Cartridge (9m2) with built in compressed air cleaning, 1-Phase/1.1kW/220V/50hz fan, circuit breaker with motor overload protection and 4m cable with plug. Order Flexi FLB- Extraction Arm separately.</p>		




Product Catalogue 2023-07-01

Art. Nr.

<p>P-543</p>	<p>MF-Eco F9 Jet-Pulse. Mobile Extractor-Filter with compressed air cleaning. 3-Phase/1.1kW/380-420V/50Hz. Incl. filterbox of powder coated steel sheet with 4 wheels with brakes, F9 filter (9m2) cartridge with built in compressed air cleaning, 3-phase/1.1kW/380-420V/50Hz fan and circuit breaker with motor overload protection and 4m cable (plug not included). Order Flexi FLB- Extraction Arm with separately.</p>		
<p>P-792</p>	<p>MF-ECO HEPA (18m2) Jet-Pulse. Mobile Extractor-Filter with F9 Prefilter (9m2) and HEPA H13/W3 Filter (9m2). 1-Phase/1.1kW/ 220V/50Hz. Incl. filter box of powder coated steel sheet with 4 wheels with brakes, F9 Prefilter (9m2) cartridge with built in compressed air cleaning, HEPA H13/W3 filter (9m2) with over 99.95% efficiency (to be replaced when full), 1-phase/ 1.1kW/220V/50Hz fan, circuit breaker with motor overload protection and 4m cable with plug. Order Flexi FLB- Extraction Arm separately.</p>		
<p>P-793</p>	<p>MF-ECO HEPA (18m2) Jet Pulse. Mobile Extractor-Filter with F9 Prefilter (9m2) and HEPA H13/W3 Filter (9m2). 3-phase 380-420V/50Hz. Incl. filter box of powder coated steel sheet with 4 wheels with brakes, F9 Prefilter (9m2) cartridge with built in compressed air cleaning, HEPA H13/W3 (9m2) filter with over 99.95% efficiency (to be replaced when full), 3-phase/ 1.1kW/380-420V/50Hz fan, circuit breaker, motor overload protection and 4m cable (plug not included). Order Flexi FLB- Extraction Arm separately.</p>		
<p>P-069</p>	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		<p>d.160mm</p>
<p>P-168</p>	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		 <p>Flexi FLB Table 1.5-3m</p>
<p>P-169</p>	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		







Product Catalogue 2023-07-01

Art. Nr.

P-167	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		<p>d.200 mm</p>  <p>Flexi FLB Table 1.5-3m</p>
P-170	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		
P-171	<p>Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		
P-086	<p>Holder for 2 Flexi FLB Arms d. 160mm for Mobi-Flex and MF-Eco.</p>		
P-928	<p>MF Filter-Table/High F9 Filter Cartridge (12m2) with 4 heavy duty Castors with Brakes. Table 600(W)x700(D)x4mm. Fixed Working Height 990mm. Fan 1.1Kw/1-Phase/220V/50Hz, Incl. powder painted Filter- and Fan box. 4mm thick unpainted steel table. 4 heavy duty Castors with Brakes (125mm High), Filter Cartridge F9 (12M2), Fan with 1.1Kw/1-phase/220V/50 Hz motor, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately.</p>		
P-935	<p>MF Filter-Table/High F9 Filter Cartridge (12m2) with 4 heavy duty Castors with Brakes. Table 900(W)x700(D)x4mm. Fixed Working Height 990mm. Fan 1.1Kw/1-Phase/220V/50Hz, Incl. powder painted Filter- and Fan box. 4mm thick unpainted steel table. 4 heavy duty Castors with Brakes (125mm High), Filter Cartridge F9 (12M2), Fan with 1.1Kw/1-Phase/220V/50 Hz motor, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" Shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm/ high (P-938). Order Shields separately.</p>		








Product Catalogue 2023-07-01

Art. Nr.

<p>P-933</p>	<p>MF Filter-Table/High HEPA H13/W3 Filter (9m2) with 4 heavy duty Castors with Brakes. Table 600(W)x700(D)x4mm. Fixed Working Height 990mm. Fan 1.1Kw/1-fase/220V/50Hz, Incl. powder painted Filter- and Fan box. 4mm thick unpainted steel table. 4 heavy duty Castors with Brakes (125mm High), Filter HEPA H13/W3 (9M2), Fan with 1.1Kw/1-phase/220V/50 Hz motor, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately.</p>		
<p>P-939</p>	<p>MF Filter-Table/High HEPA H13/W3 Filter (9m2) with 4 heavy duty Castors with Brakes. Table 900(W)x700(D)x4mm. Fixed Working Height 990mm. Fan 1.1Kw/1-Phase/220V/50Hz, Incl. powder painted Filter- and Fan box. 4mm thick unpainted steel table. 4 heavy duty Castors with Brakes (125mm High), Filter HEPA H13/W3 (9M2), Fan with 1.1Kw/1-Phase/220V/50 Hz motor, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" Shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm/ high (P-938). Order Shields separately.</p>		
<p>P-930</p>	<p>Back- and Side Shields 200mm/8" high for table 600(W)x700(D)mm (24"x28"). Powder painted and with "Quick Release" of the Sides Shields.</p>		
<p>P-931</p>	<p>Back- and Side Shields 400mm/16" high for table 600(W)x700(D)mm (24"x28"). Powder painted and with "Quick Release" of the Sides Shields. Prepared for fluorescent Lamp.</p>		
<p>P-937</p>	<p>Back- and Side Shields 200mm/8" high for table 900(W)x700(D)mm (36"x28"). Powder painted and with "Quick Release" of the Sides Shields.</p>		
<p>P-938</p>	<p>Back- and Side Shields 400mm/16" high for table 900(W)x700(D)mm (36"x28"). Powder painted and with "Quick Release" of the Sides Shields. Prepared for fluorescent Lamp.</p>		





Product Catalogue 2023-07-01

Art. Nr.

<p>P-567</p>	<p>MF-Grinder Jet-Pulse Downdraft Table with Legs, F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.9m(W)x0.6m(D)x6mm. Height 0.85m. 1-Phase/1.1kW/220V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet, 6mm thick unpainted steel table, 4 Castors with brakes, spark trap for water, F9 filter cartridge with built in compressed air cleaning, 1-Phase/1.1kW/220V//50Hz fan, circuit breaker with overload protection and 4m cable with plug. Built in flouroscent light in the upper part. Suitable for light welding and grinding.</p>		
<p>P-568</p>	<p>MF-Grinder Jet-Pulse Downdraft Table with Castors, F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.9m(W)x0.6m(D)x6mm. Height 0.85m. 3-Phase/1.1kW/380-420V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet, 6mm thick Unpainted steel table, 4 castors with brakes, spark trap for water, F9 filter cartridge with built in compressed air cleaning, 3-phase/1.1kW/380-420V/50Hz fan and circuit breaker with overload protection (cable not incl.). Built in flouroscent light in the upper part. Suitable for light welding and grinding.</p>		
<p>P-160</p>	<p>Replacement F9 Filter Cartridge (12m2) for Wall-Flex and all MF Models (Not Low).</p>		
<p>P-541</p>	<p>Replacement F9 Filter Cartridge (9m2) for WF-Eco, CF-Eco, MF-Grinder and all other Eco Models.</p>		
<p>P-544</p>	<p>Replacement HEPA H13/W3 Filter (9m2). For MF-ECO, MF-ECO HEPA, CF-ECO, CF-ECO HEPA and MF-ECO Filter-Tables/High.</p>		
<p>P-967</p>	<p>HEPA H13/W3 Filter Box 9m2 for MF, CF, MF-Filter Tables (High/Low).</p>		
<p>P-555</p>	<p>Jet-Cleaner Filter Cartridge cleaner for Mobi-Flex and Wall-Flex filter cartridges. Incl. powder painted casing of steel sheet, 4 wheels (2 with brakes), Jet-Pulse compressed air cleaning. Suitable for cleaning of Mobi-Flex and Wall-Flex filter cartridges (P-160).</p>		

Product Catalogue 2023-07-01

Art. Nr.

<h3>3.3 Wall-Filters for Light Welding/Soldering, Fume and Light Dust.</h3>			
P-026	<p>Wall-Flex F9 with F9 Filter Cartridge (12m2). For Wall Mounting. Incl. powdercoated Filterbox of steel sheet with Wall bracket, F9 Filter Cartridge (12m2), Fan Adapter and d.160mm Adapter for connecting to Central Extractor System. Can be equipped with Fan P-013 or P-015 (Fan not included). Flexi FLT (1.5-3m) or Super-Max SMT (1.5-3m) Extraction Arm can be mounted directly to the bottom side of the filterbox. Longer Extraction Arms and Extraction Cranes are to be mounted on the wall (Extraction Arm not included). Order Extraction Arm and Fan separately.</p>		
P-013	<p>P-Max Fan TURBO 0.75 kW/3-Phase/2100m3/230V/400V/50Hz/440V/60Hz. <i>Must not be run free blowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.</p>		
P-015	<p>P-Max Fan TURBO 0.75 kW/1-Phase/2100m3/220V/50Hz. <i>Must not be run free blowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi-and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels.</p>		
P-549	<p>WF-Eco F9 Jet-Pulse. Wall Mounted Extractor Filter with Compressed Air Cleaning. 1-Phase/1.1kW/220V/50Hz. Incl. powder coated filterbox of steel sheet with Wall bracket, F9 Filter cartridge (9m2) with built in compressed air cleaning, 1-phase/1.1kW/220V/50Hz Fan, circuit breaker with overload protection and 4m cable with plug. Flexi FLT (1.5-3m) or SMT (1.5m-3m) Extraction Arm can be mounted directly to the bottom side of the filterbox. Longer Extraction Arms and Extraction Cranes are be mounted on the wall (Extraction Arm not included). Can be equipped with HEPA H13/W3 Filter Box (P-554) for Stainless Steel welding (HEPA Filter is not included and HEPA Adapter P-533 is needed). Order Extraction Arm, HEPA Filter and HEPA Filter Adapter separately.</p>		





Product Catalogue 2023-07-01

Art. Nr.

<p>P-547</p>	<p>WF-Eco F9 Jet-Pulse. Wall Mounted Extractor Filter with Compressed Air Cleaning. 3-Phase/1.1kW/380-420V/50Hz. Incl. powder coated filterbox of steel sheet with Wall bracket, F9 Filter cartridge (9m²) with built in compressed air cleaning, 3-phase/1.1kW/380-420V/50Hz Fan and circuit breaker with overload protection (cable not incl). Flexi FLT (1.5-3m) or SMT (1.5-3m) Extraction Arm can be mounted directly to the bottom side of the filterbox. Longer Extraction Arms and Extraction Cranes are to be mounted on the wall (Extraction Arm not included). Can be equipped with HEPA H13/W3 Filter Box (P-554) for light Stainless Steel welding (HEPA Filter is not included and HEPA Adapter P-553 is needed). Order Extraction Arm, HEPA Filter och HEPA Adapter separately.</p>		
<p>P-051</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		<p>Ø160mm</p>
<p>P-052</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		
<p>P-053</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.</p>		
<p>P-056</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		<p>Ø200mm</p>
<p>P-057</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		
<p>P-058</p>	<p>Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.</p>		

Product Catalogue 2023-07-01





Art. Nr.

P-085	Wall-Flex Holder for Activated Carbon Filter Fleece.		
P-107	Wall-Flex. Activated Carbon Filter Fleece. 10 Pcs.		
P-160	F9 Exchange Filter Cartridge (12m2) for Wall-Flex and all MF Models (Not Low).		
P-552	Silencer for WF-Eco		
P-553	WF-Eco HEPA Filter Adapter. Needed to mount HEPA Filter on top of the WF-Eco filterbox.		
P-554	WF-Eco HEPA H13/W3 Filterbox (23m2).		
P-541	F9 Exchange Filter Cartridge (9m2) for WF-Eco, all MF-Eco Models, CF-Eco, CF-Eco Hepa and MF-Grinder.		
P-555	Jet-Cleaner Filter Cartridge cleaner for Mobi-Flex and Wall-Flex filter cartridges. Incl. powder painted casing of steel sheet, 4 wheels (2 with brakes), Jet-Pulse compressed air cleaning. Suitable for cleaning of MF and Wall-Flex filter cartridges (P-160).		

Product Catalogue 2023-07-01






Art. Nr.

**3.4 Stationary and Central Extractor Filters.
 Welding/Soldering Fume and Light Dust.**

<p>P-963</p>	<p>CF-F9. Central Extractor Filter. F9 Filter Cartridge (12m2). 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, F9 filter cartridge (12m2), 1-Phase/1.1kW/220V/50Hz Fan, circuit breaker with overload protection and 4m cable with plug. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering or light dust. Inlet diameter 200mm. Extraction Arms not included.</p>		<p>CF-F9</p> 
<p>P-964</p>	<p>CF-F9. Central Extractor Filter. F9 Filter Cartridge (12m2). 3-Phase/1.1kW/400V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, F9 filter cartridge (12m2), 3-Phase/1.1kW/400V/50Hz Fan and circuit breaker with overload protection (cable not included). Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering or light dust. Inlet diameter 200mm. Extraction Arms not included.</p>		
<p>P-965</p>	<p>CF-HEPA. Central Extractor Filter. HEPA H13/W3 Filter Box (9m2). 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder painted steel sheet, 0.5m legs, HEPA H13/W3 Filter Box (9m2), 1-Phase/1.1kW/220V/50Hz Fan, circuit breaker with overload protection and 4m cable with plug. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light Stainless Steel welding or 4-8 Extraction Arms d.75-100mm by light Stainless Steel soldering or light dust. Inlet diameter 200mm. Extraction Arms not included.</p>		<p>CF-HEPA</p> 
<p>P-966</p>	<p>CF-HEPA. Central Extractor Filter. HEPA H13/W3 Filter Box (9m2). 3-Phase/1.1kW/400V/50Hz. Incl. filterbox of powder painted steel sheet, 0.5m legs, HEPA H13 Filter Box (9m2), 3-Phase/1.1kW/400V/50Hz Fan and circuit breaker with overload protection (cable not included). Suitable as central filter for 1-2 Extraction Arms d.160 mm by light Stainless Steel welding or 4-8 Extraction Arms d.75-100mm by light Stainless Steel soldering or light dust. Inlet diameter 200mm. Extraction Arms not included.</p>		






Product Catalogue 2023-07-01

Art. Nr.

<p>P-560</p>	<p>CF-ECO F9 Jet-Pulse. Central Extractor Filter with Compressed Air Cleaning. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, F9 Filter Cartridge (9m2) with Jet-Pulse compressed air cleaning, 1-Phase/220V/1.1kW/50Hz Fan, circuit breaker with overload protection and 4m cable with plug. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering. Inlet dia. 200mm. Extraction Arms not included.</p>		<p>CF-ECO</p> 
<p>P-561</p>	<p>CF-ECO F9 Jet-Pulse. Central Extractor Filter with Compressed Air Cleaning. 3-Phase/1.1kW/400V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, F9 Filter Cartridge (9m2) with Jet-Pulse compressed air cleaning, 3-Phase/1.1kW/400V/50Hz Fan and circuit breaker with overload protection. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering. Inlet dia. 200mm. Extraction Arms not included.</p>		
<p>P-968</p>	<p>CF-ECO HEPA H13/W3 Jet-Pulse. Central Extractor Filter with Compressed Air Cleaning. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, Pre-Filter F9 Filter Cartridge (9m2) with Jet-Pulse compressed air cleaning, HEPA H13/W3 Filter Box (9m2), 1-Phase/220V/1.1kW/50Hz Fan, circuit breaker with overload protection and 4m cable with plug. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering. Inlet dia. 200mm. Extraction Arms not included.</p>		<p>CF-ECO HEPA</p> 
<p>P-969</p>	<p>CF-ECO HEPA H13/W3 Jet-Pulse. Central Extractor Filter with Compressed Air Cleaning. 3-Phase/1.1kW/400V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, Pre-Filter F9 Filter Cartridge (9m2) with Jet-Pulse compressed air cleaning, HEPA H13/W3 Filter Box (9m2), 3-Phase/1.1kW/400V/50Hz Fan and circuit breaker with overload protection. Suitable as central filter for 1-2 Extraction Arms d.160 mm by light welding or 4-8 Extraction Arms d.75-100mm by soldering. Inlet dia. 200mm. Extraction Arms not included.</p>		
<p>P-160</p>	<p>F9 Exchange Filter Cartridge (12m2) for Wall-Flex and all MF-Extractor Filters (Not Low Filter-tables)</p>		





Product Catalogue 2023-07-01

Art. Nr.

P-541	F9 Replacement Filter Cartridge for WF-Eco, MF-Eco, MF-Eco/Hepa, CF-Eco, CF-Eco/Hepa and MF-Grinder.		
P-544	HEPA H13/W3 Filter Box 9m2 for MF-Eco, MF-Eco HEPA, CF-Eco and CF-Eco/Hepa.		
P-967	HEPA H13/W3 Filter Box 9m2 for MF, CF, MF-Filter Tables (High/Low).		
P-747	Centra-Flex 50 för 2.000-5.000m³/h. Incl. Filterbox of powder painted steel sheet, wastebin with wheels exenter release and handle, 8 filter cartridges of 7 m ² each (56 m ²), compressed air tank with cleaning valves and controller. Fan to be ordered separately.		
P-748	Centra-Flex 100 för 4.000-10.000m³/h. Incl. Filterbox of powder painted steel sheet, wastebin with wheels exenter release and handle, 16 filter cartridges of 7 m ² each (112 m ²), compressed air tank with cleaning valves and controller. Fan to be ordered separately.		
P-749	Centra-Flex 150 för 6.000-15.000m³/h. Incl. Filterbox of powder painted steel sheet, wastebin with wheels exenter release and handle, 24 filter cartridges of 7 m ² each (168 m ²), compressed air tank with cleaning valves and controller. Fan to be ordered separately.		
P-750	Centra-Flex 200 för 8.000-20.000m³/h. Incl. Filterbox of powder painted steel sheet, wastebin with wheels exenter release and handle, 32 filter cartridges of 7 m ² each (224 m ²), compressed air tank with cleaning valves and controller. Fan to be ordered separately.		



Product Catalogue 2023-07-01

Art. Nr.

<p>3.5 Extractor Filters for Gases. Mobile, Wallmounted and Stationary. Active Carbon 15Ltr/7kg or 30Ltr/15kg.</p>			
P-959	<p>MF- AC 30. Mobile Extractor-Filter with 30Ltr/15kg Active Carbon Filter Cartridge. 1-Phase/1.1kW/220V/50Hz. For Gases. Incl. filterbox of powder coated steel sheet, 4 heavy duty Castors with brakes, 30Ltr/15kg Active Carbon Filter Cartridge with Prefilter Fleece, 1-phase/1.1kW/220V/50Hz fan, circuit breaker with motor overload protection and 4m cable with plug. Order Flexi FLB- Extraction Arm separately.</p>		<p>Active Carbon 30Ltr</p> 
P-960	<p>Wall-Flex Active Carbon. Wallfilter Box with 30Ltr/15kg Active Carbon Filter-Cartridge. Incl. powdercoated filterbox made of steel sheet with Wall bracket, 30Ltr/15kg Active Carbon filter cartridge with Prefilter Fleece and adapter for Fan P-013 or P-015 (Fan not included). Flexi FLT 1.5-3m and Super-Max SMT 1.5-3m extraction arms (not included) can be mounted directly to the bottom side of the filterbox. Other extraction arms and extraction cranes are to be mounted on the wall. Order Fan and Flexi FLT Extraction Arm Separately. Look Below.</p>		<p>Active Carbon 30Ltr</p> 
P-970	<p>CF-Active Carbon. Central Extractor Filter with 30Ltr/15kg Active Carbon Filter Cartridge. 1-Phase/1.1kW/220V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, Active Carbon 30Ltr/15kg Filter Cartridge with Pre-Filter Fleece, 1-Phase/1.1kW / 220V/50Hz, circuit breaker with overload protection and 4m cable with plug. Suitable as central filter for 1-2 Extraction Arms d.160 mm or 4-8 Extraction Arms d.75-100mm. Inlet diameter 200mm. Extraction Arms not included.</p>		<p>Active carbon 30Ltr</p> 
P-971	<p>CF-Active Carbon. Central Extractor Filter with 30Ltr/15kg Active Carbon Filter Cartridge. 3-Phase/1.1kW/400V/50Hz. Incl. filterbox of powder painted steel sheet with 0.5m legs, Active Carbon 30Ltr/15kg Filter Cartridge with Pre-Filter Fleece, 3-Phase/1.1kW / 220V/50Hz, circuit breaker with overload protection (no cable included). Suitable as central filter for 1-2 Extraction Arms d.160 mm or 4-8 Extraction Arms d.75-100mm. Inlet diameter 200mm. Extraction Arms not included.</p>		





Product Catalogue 2023-07-01

Art. Nr.

P-069	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		
P-168	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		 Flexi FLB Table 1.5-3m
P-169	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		d.160mm
P-167	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		 Flexi FLB Table 1.5-3m
P-170	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		d.200mm
P-171	Flexi FLB Table/Mobile Filter Extraction Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		
P-086	Holder for 2 Flexi FLB Arms d. 160mm for MF-Mobile Filters and MF-Eco Mobile Filters.		

Product Catalogue 2023-07-01

Art. Nr.

P-013	P-Max Fan TURBO 3-Phase/0.75 kW/400V/50Hz <i>Must not be run free blowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose reels		
P-015	P-Max Fan TURBO 1-Phase/0.75 kW/220V/50Hz <i>Must not be run freeblowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure), for mounting directly on to the Wall-Bracket of Flexi and Super-Max SMSV Extraction Arms, for mounting on Exhaust-Hose Wall-Brackets and on Fan-Bracket of Extractor-Cranes, on Wall-Flex and Exhaustgas Hose-Reels.		
P-051	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		
P-052	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		
P-053	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 160mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position.		Ø160mm
P-056	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/1.5m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-057	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/2m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		
P-058	Flexi FLT Ceiling/Wallfilter Extraction Arm with turning flange d. 200mm/3m. Incl. turning flange, hose and hood with damper. 8 holes for M8 bolts in the flange. C/c 230mm. Inside parallelogram technology. Incredibly easy to move and stays in position. Prepared for Lamp cartridge in the hood.		Ø200mm

Product Catalogue 2023-07-01

Art. Nr.



P-962	Replacement Active Carbon Filter Cartridge 30Ltr/15kg with Pre-Filter Fleece Outside. For MF High Models, CF and WF (Not ECO).		
-------	---	--	--

Product Catalogue 2023-07-01

Art. Nr.







4. Filter-Tables. Dust, Welding/Soldering, Fume and Gases. Sitting (Low) or Standing (High) Work Position.

4.1 Filter-Tables/Low. F9 or HEPA H13/W3 Filter. Sitting(Low) Work Position. Light Dust and Light Welding/Soldering Fume.

<p>P-972</p>	<p>MF-F9 Filter-Table/Low (0.65-0.8m) with Legs. F9 Filter Box (10m2). <i>Table 0.6m(W)x0.7m(D)x4mm.</i> For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, F9 Filter Box (10M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Table 0.6x0.7m Sitting Height 0.65-0.8m F9</p>
<p>P-974</p>	<p>MF-HEPA Filter-Table/Low (0.65-0.8m) with Legs. HEPA H13/W3 Filter Box (9m2). <i>Table 0.6m(W)x0.7m(D)x4mm.</i> For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, HEPA H13/W3 Filter Box (9M2), Fan 1-Phase/1.1Kw/ 220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Table 0.6x0.7m Sitting Height 0.65-0.8m HEPA</p>



Product Catalogue 2023-07-01

Art. Nr.

<p>P-973</p>	<p>MF-F9 Filter-Table/Low (0.65-0.8m) with Legs. F9 Filter Box (10m2). Table 0.9m(W)x0.7m(D)x4mm. For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, F9 Filter Box (10M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Table 0.9x0.7m Sitting Height 0.65-0.8m F9</p>
<p>P-975</p>	<p>MF-HEPA Filter-Table/Low (0.65-0.8m) with Legs. HEPA H13/W3 Filter Box (9m2). Table 0.9m(W)x0.7m(D)x4mm. For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, HEPA H13/W3 Filter Box (9M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Table 0.9x0.7 Sitting Height 0.65-0.8m HEPA</p>
<p>P-930</p>	<p>Back- and Side Shields 200mm High for Table 0.6m(W)x0.7m(D)mm. Powder painted and with "Quick Release" of the Sides Shields.</p>		
<p>P-931</p>	<p>Back- and Side Shields 400mm High for Table 0.6m(W)x0.7m(D). Powder painted and with "Quick Release" of the Side Shields. Prepared for fluorescent Lamp.</p>		
<p>P-937</p>	<p>Back- and Side Shields 200mm High for Table 0.9m(W)x0.7m(D). Powder painted and with "Quick Release" of the Side Shields.</p>		
<p>P-938</p>	<p>Back- and Side Shields 400mm High for Table 0.9m(W)x0.7m(D). Powder painted and with "Quick Release" of the Side Shields. Prepared for fluorescent Lamp.</p>		

Product Catalogue 2023-07-01



Art. Nr.

P-932	Holder for Welding Gun. Can be mounted to the right/left of all MF and MF-Eco Filter tables		
P-956	Heavy Duty Castors 4pcs with Brakes. For all MF Models. For mounting direct on Box or on Legs.		
P-976	F9 Replacement Filter Box 10m2. For MF Filter-Tables/Low.		
P-967	Replacement HEPA H13/W3 Filter Box 9m2. For MF, CF and MF-Filter Tables (High/Low).		

Product Catalogue 2023-07-01

Art. Nr.

**4.2 Filter-Tables/High. F9 or HEPA H13/W3 Filter.
 Standing (High) Work Position.
 Light Dust and Light Welding/Soldering Fume.**

<p>P-929</p>	<p>MF-F9 Filter-Table/High (0.85m-1m) with Legs. F9 Cartridge (12m2). Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, F9 Cartridge (12M2),Fan-1Phase/1.1kW/220V/50Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		<p>F9/High/0.6m(W)</p> 
<p>P-934</p>	<p>MF-HEPA Filter-Table/High (0.85-1m) with Legs. HEPA H13/W3 Filter Box (9m2). Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, HEPA H13/W3 Filter Box (9M2),Fan 1-Phase/1.1Kw /220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		<p>HEPA H13/W3</p> 




Product Catalogue 2023-07-01

Art. Nr.

<p>P-936</p>	<p>MF-F9 Filter-Table/High (0.85-1m) with Legs. F9 Cartridge (12m2). Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, F9 Cartridge (12M2), Fan 1-Phase/1.1kW/ 220V/50Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		<p>F9/High/0.9m(W)</p> 
<p>P-940</p>	<p>MF-HEPA Filter-Table/High (0.85-1m) with Legs. HEPA H13/W3 Filter Box (9m2). Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick unpainted steel table, HEPA H13/W3 Filter Box (9M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Spark Trap, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		<p>HEPA H13/W3</p> 
<p>P-930</p>	<p>Back- and Side Shields 200mm High for Table 0.6m(W)x0.7m(D). Powder painted and with "Quick Release" of the Side Shields.</p>		
<p>P-931</p>	<p>Back and Side Shields 400mm High for Table 0.6m(W)x0.7m(D). Powder painted and with "Quick Realise" of the Side Shields. Prepared for Flouroscent Lamp.</p>		
<p>P-937</p>	<p>Back and Side Shields 200mm High for Table 0.9m(W)x0.7m(D). Powder painted and with "Quick Release" of the Side Shields.</p>		

Product Catalogue 2023-07-01

Art. Nr.

P-938	Back and Side Shields 400mm High for Table 0.9(W)x0.7m(D). Powder painted and with “Quick Release” of the Side Shields. Prepared for Flouroscent Lamp.		
P-160	Replacement Filter Cartridge F9 (12m2) for WF and all MF Models (High).		
P-967	Replacement HEPA H13/W3 Filter Box 9m2 for MF, CF, MF Filter-Tables (High/Low).		
P-932	Holder for Welding Gun. Can be mounted to the Left or Right on all MF and MF-ECO Filter Tables.		
P-956	Heavy Duty Castors 4pcs with Brakes. For all MF Models.		

Product Catalogue 2023-07-01






Art. Nr.

**4.3 Filter-Tables for Gases/Odours.
 Active Carbon Filter Cartridge 15Ltr or 30Ltr.
 Sitting/Low or Standing/High Work Position.**

<p>P-977</p>	<p>MF-AC Filter-Table/Low (0.65-0.8m) with Legs. Active Carbon Filter Cartridge (15Ltr/7kg) Table 0.6m(W)x0.7m(D)x4mm. For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs, Steel Table 0.6mx0.7m x4mm, Active Carbon Filter Cartridge (15Ltr/7kg) with Pre-Filter Fleece outside, Fan 1-Phase/1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon/15Ltr Low/0.6m(W)</p>
<p>P-978</p>	<p>MF-AC Filter-Table/Low (0.65-0.8m) with Legs. Active Carbon Filter Cartridge (15Ltr/7kg) Table 0.9m(W)x0.7m(D)x4mm. For Sitting Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs, Steel Table 0.9mx0.7m x4mm, Active Carbon Filter Cartridge (15Ltr/7kg) with Pre-Filter Fleece outside, Fan 1-Phase/1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon/15Ltr Low/0.9m(W)</p>
<p>P-979</p>	<p>MF-AC Filter-Table/High (0.85-1m) with Legs. Active Carbon Filter Cartridge (30Ltr/15kg). Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs, Steel Table 0.6mx0.7m x4mm, Active Carbon Filter Cartridge (30Ltr/15kg) with Pre-Filter Fleece outside, Fan 1-Phase/1.1Kw/2 20V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-930) or 400mm high (P-931). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon/30Ltr High/0.6m(W)</p>

Product Catalogue 2023-07-01

Art. Nr.

<p>P-780</p>	<p>MF-AC Filter-Table/High (0.85-1m) with Legs. Active Carbon Filter Cartridge (30Ltr/15kg) Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs, Steel Table 0.9mx0.7m x4mm, Active Carbon Filter Cartridge (30Ltr/15kg) with Pre-Filter Fleece outside, Fan 1-Phase/1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Prepared for "Quick Release" shields on top of 3 sides of the table. Shields 200mm high (P-937) or 400mm high (P-938). Order Shields separately. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon 30Ltr High/0.9m(W).</p>
<p>P-930</p>	<p>Back- and Side Shields 200mm High for Table 0.6m(W)x0.7m(D)mm. Powder painted and with "Quick Release" of the Sides Shields.</p>		
<p>P-931</p>	<p>Back- and Side Shields 400mm High for Table 0.6m(W)x0.7m(D)mm. Powder painted and with "Quick Release" of the Sides Shields. Prepared for fluorescent light.</p>		
<p>P-937</p>	<p>Back- and Side Shields 200mm High for Table 0.9m(W)x0.7m(D)mm. Powder painted and with "Quick Release" of the Sides Shields.</p>		
<p>P-938</p>	<p>Back- and Side Shields 400mm High for Table 0.9m(W)x0.7m(D)mm. Powder painted and with "Quick Release" of the Sides Shields. Prepared for fluorescent light.</p>		
<p>P-956</p>	<p>Heavy Duty Castors 4pcs with Brakes. For all MF Models. Mounting direct on Box or on Legs.</p>		
<p>P-961</p>	<p>Replacement Active Carbon Filter Cartridge 15Ltr/7kg with Pre-Filter Fleece Outside. For MF Low Models (Not ECO Models).</p>		
<p>P-962</p>	<p>Replacement Active Carbon Filter Cartridge 30Ltr/15kg with Pre-Filter Fleece Outside. For MF High Models (Not ECO Models).</p>		



Product Catalogue 2023-07-01

Art. Nr.

4.4 Filter-Tables (ECO) with Jet-Pulse Cleaning. Sitting(Low) or Standing(High)Work Position. Light Dust and light Welding/Soldering Fume.			
	MF-ECO/F9 Filter-Table/Low (0.65-0.8m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.		
	MF-ECO/F9 Filter-Table/Low (0.65-0.8m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.		
	MF-ECO/F9 Filter-Table/High (0.85-1m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.		
	MF-ECO/HEPA Filter-Table/High (0.85-1m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. HEPA H13/W3 Filter Box (9m2). Table 0.6m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.		





Product Catalogue 2023-07-01

Art. Nr.

	<p>MF-ECO F9 Filter-Table/High (0.85-1m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.</p>		
	<p>MF-ECO HEPA Filter-Table/High (0.85-1m) Legs. F9 Filter Cartridge (9m2) with Jet-Pulse Cleaning. HEPA H13/W3 Filter Box (9m2). Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position. Fan 1-Phase/1.1kW/220V/50Hz.</p>		
P.565	<p>MF-Grinder Jet-Pulse Downdraft Table with Castors, F9 Filter Cartridge and Compressed Air Cleaning. 1-Phase/1.1kW/380-420V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet and a 6mm thick steel table, 4 Castors with brakes, spark trap with water, F9 filter cartridge with built in compressed air cleaning, 1-phase/1.1kW/220V/50Hz fan and circuit breaker with overload protection and cable with plug. Built in flouroscent lamp in the upper part. Suitable for Light welding and grinding.</p>		
P-566	<p>MF-Grinder Jet-Pulse Downdraft Table with Castors, F9 Filter Cartridge and Compressed Air Cleaning. 3-Phase/1.1kW/380-420V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet and a 6mm thick steel table, 4 Castors with brakes, spark trap with water, F9 filter cartridge with built in compressed air cleaning, 3-phase/1.1kW/380-420V/50Hz fan and circuit breaker with overload protection (cable not incl.). Built in flouroscent lamp in the upper part. Suitable for Light welding and grinding.</p>		

Product Catalogue 2023-07-01



Art. Nr.

P-567	MF-Grinder Jet-Pulse Downdraft Table with Castors, F9 Filter Cartridge and Compressed Air Cleaning. 1-Phase/1.1kW/380-420V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet and a 6mm thick steel table, 4 Castors with brakes, spark trap with water, F9 filter cartridge with built in compressed air cleaning, 1-phase/1.1kW/220V /50Hz fan and circuit breaker with overload protection and cable with plug. Built in flouroscent light in the upper part. Suitable for welding and grinding.		
P568	MF-Grinder Jet-Pulse Downdraft Table with Castors, F9 Filter Cartridge and Compressed Air Cleaning. 3-Phase/1.1kW/380-420V/50Hz. Incl. Filterbox and bench top of powder painted steel sheet and a 6mm thick steel table, 4 Castors with brakes, spark trap with water, F9 filter cartridge with built in compressed air cleaning, 3-phase/1.1kW/380-420V/50Hz fan and circuit breaker with overload protection (cable not incl.). Built in flouroscent light in the upper part. Suitable for welding and grinding.		
P-544	Replacement HEPA H13/W3 Filter Box 9m2 for MF-ECO, MF-ECO HEPA, CF-ECO, CF-ECO HEPA and MF-ECO Filter-Tables (Not Low Models).		
P-541	F9 Replacement Filter Cartridge for WF-Eco, MF-Eco, CF-Eco, MF-ECO Filter-Tables and MF-Grinder.		

Product Catalogue 2023-07-01



Art. Nr.

5. Oil/Coolant-Mist Extractor-Filters. Mobile, Machine mounted and Stationary.

5.1 Mobi-Oil. Mobile Oil/Coolant-Mist Extractor-Filters.			
P-603	<p>Mobi-Oil. Mobile Oil/Coolant Mist Extractor-Filter. 1-Phase/0.75kW/220V/50Hz.</p> <p>Incl. filterbox of powder painted steel sheet, 4 Heavy Duty Castors with brakes, labyrinth filter, cassette filter of nailed glass-fiber, HEPA H13 filter, 2 plastic containers for separated oil with quick connections, 1-phase/220V/0.75kW/50Hz fan, circuit breaker with overload protection and 4m cable with plug. Suitable for oilmist from coolants.</p> <p>Extraction Arm 2m (P-606) or 3m (P-607) has to be ordered separately.</p>		
P-604	<p>Mobi-Oil mobile Oilmist Filter. 3-Phase/0.75kW/380-420V/50Hz. Incl. filterbox of powder painted steel sheet, 4 wheels (2 with brakes), labyrinth filter, cassette filter of nailed glassfiber, HEPA filter, 2 plastic containers for separated oil with quick connections, 3-phase/380-420V/0.75kW/50Hz fan, circuit breaker with overload protection (cable not included). Suitable for oilmist from coolants.</p> <p>Extractor arm 2m (P-606) or 3m (P-607) has to be ordered separately</p>		
P-606	<p>Flexi Oilmist Extractor arm 2m for Mobi-Oil. Diameter 160mm. Standing with turning flange. Damper in Hood.</p>		
P-607	<p>Flexi Oilmist Extractor arm 3m for Mobi-Oil. Diameter 160mm. Standing with turning flange. Damper in Hood.</p>		
P-596	<p>Replacement HEPA H13 (9m2) Filter for Mobi-Oil.</p>		
P-600	<p>Replacement Cassette Filter for Mobi-Oil and NX-600.Nailed glass-fiber with aluminum separators 4.5m2 (4.5+4.5m2).</p>		





Product Catalogue 2023-07-01

Art. Nr.

5.2 FLX. Machine mounted Oil/Coolant-Mist Extractor-Filters. 600m3/h and 1100m3/h.			
P-268	FLX-600 Filter for Coolant- and Oilmist with fan. Incl. powder coated filterbox of steel sheet, 3-phase 0.75 kW /380-420V/50Hz fan, inlet chamber with pre-separator, 2 aluminium mesh filters, 2 EU-5 glass-fiber fleece filters, one hydrofilter (impinger) and one HEPA-H13 filter. Built in Silencer. Aluminium mesh filters and Hydrofilter are washable. Noise level 63dB(A).		
P-269	FLX-1100 Filter for Coolant- and Oilmist with fan. Incl. powder coated filterbox of steel sheet, 3-phase 1,1 kW /380-420V/50Hz fan, inlet chamber with pre-separator, 2 aluminium mesh filters, 2 EU-5 glasfibre fleece filters, one hydrofilter (impinger) and one HEPA-filter. Built in Silencer. Aluminium mesh filters and Hydrofilter are washable. Noise level 63dB(A).		
P-392	Pressure-gauge (Manometer) for FLX-600/1100. 2 Pcs mounted in the Door.		
P-313	Replacement Filter Fleece EU-5 for FLX-600. Set of 10 Pcs.		
P-314	Replacement Filter Fleece EU-5 for FLX-1100. Set of 10 Pcs.		
P-316	Replacement Filter HEPA H13 (99.95%) for FLX-600.		
P-317	Replacement Filter HEPA H13 (99.95%) for FLX-1100.		
P-307	Sparepart: Aluminum Mesh filter for FLX-600.		
P-308	Sparepart: Aluminum Mesh filter for FLX-1100.		
P-310	Sparepart: Hydrofilter (Impinger) for FLX-600.		
P-311	Sparepart: Hydrofilter (Impinger) for FLX-1100.		






Product Catalogue 2023-07-01

Art. Nr.

5.3 NX Stationary Oil/Coolant-Mist Extractor-Filters. Models 400m³/h-8000m³/h. Machine, Wall or Central mounting.			
P-588	NX-400 Oilmist Filter. 1-Phase/0.37kW/220V/50Hz. Incl. filterbox of powder painted steel sheet, labyrinth filter, cassette filter of nailed glass-fiber, 1-phase/220V/0.37kW/50Hz fan, inlet diameter 160mm with lockable damper, circuit breaker with overload protection and 4m cable with plug. Suitable for oilmist from coolants. Can be equipped with HEPA filter P-595 (To be ordered separately).		
P-590	NX-400 Oilmist Filter. 3-Phase/0.37kW/400V/50Hz. Incl. filterbox of powder painted steel sheet, labyrinth filter, cassette filter of nailed glass-fiber, 3-phase/380-420V/0.37kW/50Hz fan, inlet diameter 160mm with lockable damper. Electric Connection box outside. Suitable for oilmist from coolants. Can be equipped with HEPA filter P-595 (To be ordered separately).		
P-592	NX-600 Oilmist Filter. 1-Phase/0.75kW/220V/50Hz. Incl. filterbox of powder painted steel sheet, labyrinth filter, cassette filter of nailed glass-fiber, 1-phase/220V/0.75kW/50Hz fan, inlet diameter 160mm with lockable damper, circuit breaker with overload protection and 4m cable with plug. Suitable for oilmist from coolants. Can be equipped with HEPA filter P-596 (To be ordered separately).		
P-594	NX-600 Oilmist Filter. 3-Phase/0.75kW/400V /50Hz. Incl. filterbox of powder painted steel sheet, labyrinth filter, cassette filter of nailed glassfiber, 3-phase/380-420V/0.75kW/50Hz fan, inlet diameter 160mm with lockable damper. Electric Connection box outside. Suitable for oilmist from coolants. Can be equipped with HEPA filter P-596 (To be ordered separately).		
P-595	HEPA H13 Filter for NX-400 (6m²).		
P-596	HEPA H13 Filter for NX-600 (9m²).		
P-597	Legs for NX-400/600. 4 Pcs. 0.2m.		
P-598	Legs for NX-400/600. 4 Pcs. 0.4m.		
P-599	Replacement Nailed Glass-Fiber Filter Cassette for NX-400. Nailed glass-fiber with aluminum separators 3m ² .		
P-600	Replacement Nailed Glass-Fiber Filter Cassette for NX-600. Nailed glass-fiber with aluminum separators 4.5m ² .		




Product Catalogue 2023-07-01

Art. Nr.

P-624	<p>NX-1000 Filter <u>without Fan</u> for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 160mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 160mm (inside measure), filter cassette (8m² EU-5/9) of nailed glass-fiber, HEPA H13 filter 22m² and 2 pcs pressure gauges (manometers).</p>		
P-631	<p>NX-2000 Filter <u>without Fan</u> for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 200mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 200mm (inside measure), 2 filter cassettes (10m² EU-5) and (8m² EU-5/9) of nailed glass-fiber, HEPA H13 filter 22m² and 3 pcs pressure gauges (manometers).</p>		
P-633	<p>NX-4000 Filter <u>without Fan</u> for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 315mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 315mm (inside measure), 2 filter cassettes of nailed glass-fiber (21 m² EU-5) and (15 m² EU-9), HEPA H13 filter 44 m² and 3 pcs pressure gauges(manometers).</p>		
P-635	<p>NX-6000 Filter <u>without Fan</u> for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 400mm (inside measure), 3 filter cassettes of nailed glass-fiber (10m² EU-5 each) and 3 pcs (8m² EU-5/9), 3 HEPA H13 filters (22m² each) and 9 pcs pressure gauges(manometers).</p>		
P-639	<p>NX-8000 Filter <u>without Fan</u> for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, outlet flange 400mm (inside measure), 2 filter cassettes of nailed glass-fiber (21m² EU-5 each) and 2 pcs (15m² EU-9 each), 2 HEPA H13 filters (44m² each) and 6 pcs pressure gauges(manometers).</p>		
P-259	<p>NX-1000 Filter <u>with Fan</u> 3-phase/1,1 kW/400V/50Hz for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 160mm inlet flange (inside measure) and cover plate for the not used inlet side, fan 3-phase/1,1 kW/400V/50Hz, filter cassette (8m² EU-5/9) of nailed glass-fiber, HEPA H13 filter (22m²) and 2 pcs pressure gauges (manometers).</p>		

Product Catalogue 2023-07-01

Art. Nr.

P-260	NX-2000 Filter with Fan 3-phase/2,2 kW/400V/50Hz for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 200mm inlet flange (inside measure) and cover plate for the not used inlet side, fan 3-phase/2,2 kW/400V/50Hz, filter cassettes (10m ² EU-5) and (8m ² EU-5/9) of nailed glass-fiber, HEPA H13 filter 22m ² and 3 pcs pressure gauges (manometers).		
P-261	NX-4000 Filter with Fan 3-phase/4 kW/400V/50Hz for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 315mm inlet flange (inside measure) and cover plate for the not used inlet side, fan 3-phase/4 kW/400V/50Hz, filter cassettes (21 m ² EU-5) and (15 m ² EU-9) of nailed glass-fiber, HEPA H13 filter 44m ² and 3 pcs pressure gauges (manometers).		
P-636	NX-6000 Filter with Fans 3-phase/3x2,2 kW/400V/50Hz for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, fan 3-phase/3x2,2kW/400V/50Hz, filter cassettes 3x10m ² Eu-5 and 3x8m ² EU-5/9 of nailed glass-fiber, HEPA H13 filter 3x22m ² and 9 pcs pressure gauges (manometers).		
P-640	NX-8000 Filter with Fans 3-phase/2x4 kW/400V/50Hz for Coolant and Oilmist incl. filterbox and legs of powder painted steel sheet, oil return pipe with 1" outside thread, inlet from the right or left with 400mm inlet flange (inside measure) and cover plate for the not used inlet side, fan 3-phase/2x4 kW/400V/50Hz, filter cassettes 2x21 m ² and 2x15 m ² of nailed glass-fiber, 2xHEPA H13 filter 44m ² and 6 pcs pressure gauges (manometers).		
P-322	Extension Legs 0.5m 4 Pcs. for NX1000/2000/4000.		
P-318	Replacement Nailed Glass-Fiber Filter Cassette (10m² EU-5). First from the bottom for NX-2000/6000 (For NX-6000 are 3 pcs. needed).		
P-319	Replacement Nailed Glass-Fiber Filter Cassette (8m² EU-5/9). Second from the bottom for NX-2000/6000 (For NX-6000 are 3 pcs. needed). This cassette is the only needed for NX-1000.		
P-320	Replacement Nailed Glass-Fiber Filter Cassette (21 m² EU-5). First from the bottom for NX-4000/8000 (For NX-8000 are 2 pcs. needed).		

Product Catalogue 2023-07-01

Art. Nr.



P-321	Replacement Nailed Glass-Fiber Filter Cassette (15 m² EU-9) Second from the bottom for NX-4000/8000 (For NX-8000 are 2pcs needed).		
P-264	Replacement HEPA H13 Filter 22m² (99,95%) for NX-1000/2000/6000 (For NX-6000 are 3 pcs needed).		
P-266	Replacement HEPA H13 Filter 44m² (99,95%) for NX-4000/8000 (For NX-8000 are 2 pcs needed).		

Product Catalogue 2023-07-01

Art. Nr.



6. Laboratory. Dust, Fume and Gases. Extraction-Arms, Extractor-Filters and Filter-Tables.

6.1 INSIDE SUPPORT. Flexa Extraction-Arms d. 75/100mm. Length 1m/1.3m/1.6m. Wall/Ceiling and Table mounting.

P-646	Flexa wall/Ceiling Extraction-Arm Ø 75/ 1m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-647	Flexa wall/Ceiling Extraction-Arm Ø 75/ 1,3m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-648	Flexa wall/Ceiling Extraction-Arm Ø 75/ 1,6m Incl. Wall bracket with turning flange, hose and hood. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-652	Flexa wall/Ceiling Extraction-Arm Ø 100/ 1m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-653	Flexa wall/Ceiling Extraction-Arm Ø 100/ 1,3m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		
P-654	Flexa wall/Ceiling Extraction-Arm Ø 100/ 1,6m Incl. Wall bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the wall with the Wall bracket and in the Ceiling by using just the turning flange.		




Product Catalogue 2023-07-01

Art. Nr.

P-649	Flexa Table Extraction-Arm Ø 75/ 1m Incl. table bracket with turning flange, hose and hood. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-650	Flexa Table Extraction-Arm Ø 75/ 1,3m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-651	Flexa Table Extraction-Arm Ø 75/ 1,6m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-656	Flexa Table Extraction-Arm Ø 100/ 1m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-657	Flexa Table Extraction-Arm Ø 100/ 1,3m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		
P-658	Flexa Table Extraction-Arm Ø 100/ 1,6m Incl. table bracket with turning flange, hose and hood. Inside parallelogram technology. Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket and on the table by using just the turning flange.		



Product Catalogue 2023-07-01

Art. Nr.

<p>6.2 OUTSIDE SUPPORT. Chemikus Extraction-Arms d. 75/100mm. Length 1m/1.3m/1.6m. Wall/Ceiling and Table mounting.</p>			
P-660	<p>Chemikus wall/ceilings Extraction-Arm Ø 75/ 1m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-661	<p>Chemikus wall/ceilings Extraction-Arm Ø 75/ 1,3m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-662	<p>Chemikus wall/ceilings Extraction-Arm Ø 75/ 1,6m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-666	<p>Chemikus wall/ceilings Extraction-Arm Ø 100/ 1m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-667	<p>Chemikus wall/ceilings Extraction-Arm Ø100/ 1,3m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-668	<p>Chemikus wall/ceilings Extraction-Arm Ø 100/ 1,6m Incl. Wall bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceilings by using just the turning flange.</p>		
P-663	<p>Chemikus Table Extraction-Arm Ø 75/1m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		







Product Catalogue 2023-07-01

Art. Nr.

P-664	Chemikus Table Extraction-Arm Ø 75/1,3m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-665	Chemikus Table Extraction-Arm Ø 75/1,6m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-669	Chemikus Table Extraction-Arm Ø 100/1m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-670	Chemikus Table Extraction-Arm Ø 100/1,3m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		
P-671	Chemikus Table Extraction-Arm Ø 100/1,6m Incl. Table bracket and turning flange, hose and hood. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.		


Product Catalogue 2023-07-01

Art. Nr.

6.3 Extractor-Filters for Dia. 75/100mm Extration-Arms.			
P-947	Labbe-400. 360 mm(W)x470 mm(D)x630 mm(H) Incl. EC Motor 0.178 kW, 1 phase/220V/50Hz, HEPA H14 Filter (8 m2), Active Coal Fleece Filter, Adjustable Speed, 4 Castors with Breakes, 4 m Cable with Plug. Inlet Box 120mm(D) with 3 Inlets downwards. Outside d.99mm each.		
P-987	Labbe-400E1F. LABBE-400E1 including 1 Top mounted Flexa d.100mm/1.3m Extraction-Arm Incl. EC Fan 1-phase/0.178kW/220V/50Hz, HEPA H14 Filter (8 m2), Active Coal Filter Fleece, Adjustable Speed, 4 Castors with Breakes, 4 m Cable with Plug. Measurements 360 mm(W)x470 mm(D) x630 mm(H) + Extraction-Arm.		
P-988	Labbe-400E2F. LABBE-400E2 including 2 Top mounted Flexa d.75mm/1.3m Extraction-Arms Incl. EC Fan 1-phase/0.178kW/220V/50Hz, HEPA H14 Filter (8 m2), Active Coal Filter Fleece, Adjustable Speed, 4 Castors with Breakes, 4 m Cable with Plug. Measurements 360 mm(W)x470 mm(D) x630 mm(H) + Extraction-Arms.		
P-948	Labbe-400/Kit 1. Complete Kit with Labbe-400 (P-947) + 1x Flexa d.100mm/1m Extraction Arm (P-649) + 1x3m/ dia.100mm Hose with 2 Hose Clamps.		
P-949	Labbe-400/Kit 2. Complete Kit with Labbe-400 (P-947) + 2x Flexa d.75mm/1m Extraction Arms (P-656) + 2x3m/dia.100mm Hose with 4xHose Clamps.		
P-950	Labbe-400/Kit 3. Complete Kit with Labbe-400 (P-947) + 3x Flexa d.75/1m Extraction Arms (P-649) + 3x3m/dia.100mm Hose with 6xHose Clamps.		
P-951	Labbe-400E1 for 1 Topmounted Extraction Arm dia.100 mm. 360 mm(W)x470 mm(D)x630 mm(H) Incl. EC Motor 0.178 kW, 1 phase/220V/50Hz, HEPA H14 Filter (8 m2), Active Coal Fleece Filter, Adjustable Speed, 4 Castors with Breakes, 4 m Cable with Plug. Topside prepared for 1 dia.100mm Flexa or Chemikus Table Extraction Arm (To be ordered separatly See 6.1 and 6.2 above)		

Product Catalogue 2023-07-01




Art. Nr.

P-952	Labbe-400E2 for 2 Topmounted Extraction Arms dia 75 mm. 360 mm(W)x470 mm(D)x630 mm(H) Incl. EC Motor 0.178 kW, 1 phase/220V/50Hz, HEPA H14 Filter (8 m2), Active Coal Fleece Filter, Adjustable Speed, 4 Castors with Breakes, 4 m Cable with Plug. Topside prepared for 2 dia.75mm Flexa or Chemikus Table Extraction Arms (To be ordered separatly See 6.1 and 6.2 above)		
P-953	Replacement Active Coal Filter Fleece (Set of 5 pcs) for Fika-Flex and Labbe-400.		
P-954	Replacement HEPA H14 Filter (8m2) for Fika-Flex, Denta-Flex and Labbe-400. EN 1822 (99.995%). With Certificate and Leak Tested. 305x305x200mm		

Product Catalogue 2023-07-01




Art. Nr.

6.4 Filter-Tables. Dust, Fume and Gases. Sitting(Low) or Standing(High) Work Position.

<p>P-981</p>	<p>MFK-F9/Low Filter-Table (0.65-0.8m) with Legs. F9 Filter Box (10m2). Table 0.6m(W)x0.7m(D)x4mm. For Sitting Work Position (0.65-0.8m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, F9 Filter Box (10M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 200mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>F9/Low/0.6m(W)</p>
<p>P-982</p>	<p>MFK-HEPA/Low Filter-Table (0.65-0.8m) with Legs. HEPA H13/W3 Filter Box (9m2). Table 0.6m(W)x0.7m(D)x4mm. For Sitting Work Position (0.65-0.8m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, HEPA H13/W3 Filter Box (9M2), Fan 1-Phase/1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 200mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>HEPA/Low/0.6m</p>
<p>P-983</p>	<p>MFK-AC/Low (Active Carbon) Filter-Table (0.65-0.8m) with Legs. Active Carbon (15Ltr/7kg) Filter Cartridge. Table 0.6m(W)x0.7m(D)x4mm. For Sitting Work Position (0.65-0.8m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, Active Carbon 15Ltr/7kg Filter Cartridge , Fan 1-Phase/ 1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 200mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon Low/0.6m(W)</p>

Product Catalogue 2023-07-01


Art. Nr.

<p>P-984</p>	<p>MFK-F9/High Filter-Table (0.85-1m) with Legs. F9 Filter Cartridge (12m2). Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position (0.85-1m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, F9 Filter Cartridge (12M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 400mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>F9/High/0.9m(W)</p>
<p>P-985</p>	<p>MFK-HEPA/High Filter-Table (0.85-1m) with Legs. HEPA H13 Filter Box (9m2). Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position (0.85-1m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, HEPA H13 (9m2) Filter Box, Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 400mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>HEPA/High/0.9m</p>
<p>P-986</p>	<p>MFK-AC/High Filter-Table (0.85-1m) with Legs. Active Carbon (30Ltr/15kg) Filter Cartridge. Table 0.9m(W)x0.7m(D)x4mm. For Standing Work Position (0.85-1m). Fan 1-Phase/1.1kW/220V/50Hz. Incl. powder painted Filter-and Fan box with 4 height adjustable Legs. 4mm thick steel table, Active Carbon Filter Cartridge with Pre-Filter Fleece, Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. "Quick Release" shields on top of 3 sides of the table. Shields 400mm high. Prepared for Heavy Duty Castors (P-956). Order Castors separately.</p>		 <p>Active Carbon 30Ltr/High/0.9m</p>
<p>P-956</p>	<p>Heavy Duty Castors 4pcs with Brakes. For all MF Models.</p>		
<p>P-961</p>	<p>Replacement Active Carbon 15Ltr/7kg Filter Cartridge with Pre-Filter Fleece. For MF Low Models (Not ECO).</p>		
<p>P-962</p>	<p>Replacement Active Carbon 30Ltr/15kg Filter Cartridge with Pre-Filter Fleece. For MF High Models (Not ECO).</p>		

Product Catalogue 2023-07-01



Art. Nr.

7. Chemistry, Pharma, Food and Laboratory. ATEX- and Stainless Steel Extraction-Arms. FILTER-TABLES.

7.1 OUTSIDE SUPPORT. ATEX Super-PM Extraction-Arms. Electrogalvanized with Hood/Handle of Stainless Steel. Dia. 110/160mm. Length 1.5m-4m. ATEX:EX II2D/G			
P-367	ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.25+1.5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-368	ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.5+1.5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-369	ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/2m (0.25+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.110mm</p>  <p>Straight Hood Super-PM 1.5-4m</p>
P-370	ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/2m (0.5+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		





Product Catalogue 2023-07-01

Art. Nr.

P-371	<p>ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/3m (0.5+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position..</p>		<p>D.110mm</p>
P-372	<p>ATEX Super-PM Extraction-Arm with "Straight Hood" d.110mm/4m (0.5+0,6+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl.wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		 <p>Straight Hood Super-PM 1.5-4m</p>
P-373	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/1.5m (0.25+1.5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-374	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/1.5m (0,5+1.5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		<p>D.110mm</p>
P-375	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/2m (0.25+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		 <p>150° Hood Super-PM 1.5-4m</p>
P-376	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/2m (0.5+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		



Product Catalogue 2023-07-01

Art. Nr.

P-377	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/3m (0.5+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		<p>D.110mm</p>  <p>150° Hood Super-PM 1.5-4m</p>
P-378	<p>ATEX Super-PM Extraction-Arm with "150° Hood" d.110mm/4m (0.5+0,6+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		 <p>150° Hood Super-PM 1.5-4m</p>
P-379	<p>ATEX Super-PM Extraction-Arm with "67° Hood" d.110mm/1,5m (0.25+1,5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		
P-380	<p>ATEX Super-PM Extraction-Arm with "67° Hood" d.110mm/1,5m (0.5+1,5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G.Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		<p>D.110mm</p>  <p>67° Hood Super-PM 1.5-4m</p>
P-381	<p>ATEX Super-PM Extraction-Arm with "67° Hood" d.110mm/2m (0.25+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G.Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		 <p>67° Hood Super-PM 1.5-4m</p>
P-382	<p>ATEX Super-PM Extraction-Arm with "67° Hood" d.110mm/2m (0.5+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		


Product Catalogue 2023-07-01

Art. Nr.

<p>P-383</p>	<p>ATEX Super-PM Extraction-Arm with "67° Hood" d.110mm/3m (0.5+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		 <p>67° Hood Super-PM 1.5-4m D.110mm</p>
<p>P-384</p>	<p>ATEX Super-PM Extraction-Arm "67° Hood" d.110mm/4m (0.5+0,6+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
<p>P-385</p>	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/1,5m (0.25+1,5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		<p>D.160mm</p>
<p>P-386</p>	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/1,5m (0.5+1,5m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		 <p>ø 160 mm Super-PM 1.5-4m</p>
<p>P-387</p>	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/2m (0.25+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		
<p>P-388</p>	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/2m (0.5+2m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		

Product Catalogue 2023-07-01


Art. Nr.

P-389	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/3m (0.5+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		<p>D.160mm ø 160 mm</p>  <p>Super-PM 1.5-4m</p>
P-390	<p>ATEX Super-PM Extraction-Arm with "45° Hood" d.160mm/4m (0.5+0.6+3m) of Electro Galvanized Steel. Hood and Handle made of mirror polished acidproof stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position</p>		
P-483	<p>Tight Damper for "Straight Hood" d.110mm. Made of acidproof Stainless Steel.</p>		
P-482	<p>Tight Damper for "67° Hood" and "150° Hood" d.110mm. Made of acidproof Stainless Steel.</p>		
P-484	<p>Tight Damper for "45° Hood d.160mm". Made of acidproof Stainless Steel.</p>		

Product Catalogue 2023-07-01


Art. Nr.

**7.2 OUTSIDE SUPPORT. ATEX Super-M
 Extraction Arms. All Parts of Mirror polished,
 Acidproof Stainless Steel. Dia. 110/160mm.
 Length 1.5m-4m. ATEX: EX II 2D/G.**

P-331	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.25+1.5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		<p>D.110mm</p>  <p>Straight Hood Super-M 1.5-4m</p>
P-332	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.5+1.5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G.Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and besterilized in an Autoclave.</p>		
P-333	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/2m (0.25+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G.Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-334	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/2m (0.5+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-335	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/3m (0.5+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		


Product Catalogue 2023-07-01

Art. Nr.

P-336	<p>ATEX Super-M Extraction-Arm with "Straight Hood" d.110mm/4m (0.5+0.6+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-337	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/1.5m (0.25+1.5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-338	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/1.5m (0.5+1.5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		<p>D.110mm</p>  <p>67° Hood</p>
P-339	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/2m (0.25+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		<p>Super-M 1.5-4m</p>
P-340	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/2m (0.5+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-341	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/3m (0.5+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		


Product Catalogue 2023-07-01

Art. Nr.

P-342	<p>ATEX Super-M Extraction-Arm with "67° Hood" d.110mm/4m (0.5+0,6+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-343	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/1,5m (0.25+1,5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX:EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-344	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/1,5m (0.5+1,5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		<p>D.110mm</p>  <p>150° Hood Super-M 1.5-4m</p>
P-345	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/2m (0.25+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-346	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/2m (0.5+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		
P-347	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/3m (0.5+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>		


Product Catalogue 2023-07-01

Art. Nr.

P-348	<p>ATEX Super-M Extraction-Arm with "150° Hood" d.110mm/4m (0.5+0.6+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>	
P-178	<p>ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/1,5m (0.25+1,5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>	
P-179	<p>ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/1,5m (0.5+1.5m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G.Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>	
P-180	<p>ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/2m (0.25+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave.</p>	<p>D.160mm</p>  <p>Super-M 1,5-4m</p>
P-181	<p>ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/2m (0.5+2m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave</p>	
P-182	<p>ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/3m (0.5+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm.</p> <p>ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave</p>	

Product Catalogue 2023-07-01


Art. Nr.

P-183	ATEX Super-M Extraction-Arm with "45° Hood" d.160mm/4m (0.5+0.6+3m) of mirror polished, acidproof Stainless Steel. Sealed Tube Ends. PVC Hose electrically conductive 10⁴ Ohm. ATEX: EX II 2D/G. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position. Can easily be taken to pieces and be sterilized in an Autoclave		 Super-M 1,5-4m
P-483	Tight Damper for "Straight Hood" d.110mm. Made of acidproof Stainless Steel.		
P-482	Tight Damper for "67° Hood" and "150° Hood" d.110mm. Made of acidproof Stainless Steel.		
P-484	Tight Damper for "45° Hood d.160mm". Made of acidproof Stainless Steel.		

Product Catalogue 2023-07-01







Art. Nr.

**7.3 OUTSIDE SUPPORT. Chemikus-PM
 Extraction Arms. Electro galvanized with
 Hood/Handle of Stainless Steel. Dia.
 75/100mm. Length 1m-1.6m.**

P-674	<p>Chemikus PM with Stainless Steel Hood/ Handle. Wall/Ceiling Extraction-Arm Ø 75/1m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange.</p>		
P-675	<p>Chemikus PM with Stainless Steel Hood/ Handle. Wall/Ceiling Extraction-Arm Ø 75/1.3m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange.</p>		
P-676	<p>Chemikus PM with Stainless Steel Hood/ Handle. Wall/Ceiling Extraction-Arm Ø 75/1.6m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange.</p>		
P-677	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 75/1m Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		
P-678	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 75/1.3m Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		


Product Catalogue 2023-07-01

Art. Nr.

<p>P-679</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 75/1.6m Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		
<p>P-680</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle Wall/Ceiling Extraction-Arm Ø 100/1m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange</p>		
<p>P-681</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle Wall/Ceiling Extraction-Arm Ø 100/1.3m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange</p>		
<p>P-682</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle Wall/Ceiling Extraction-Arm Ø 100/1.6m Incl. Wall bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the wall with the wall bracket and in the ceiling by using just the turning flange</p>		
<p>P-683</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 100/1m Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		
<p>P-684</p>	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 100/1.3m Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		

Product Catalogue 2023-07-01


Art. Nr.

P-685	<p>Chemikus PM with Stainless Steel Hood/ Handle. Table Extraction-Arm Ø 100/1.6m</p> <p>Incl. Table bracket and turning flange, hose, hood and handle of mirror polished acid proof stainless steel. External hydraulically suspended electro galvanized parallelogram arms. "Free blow in the hose". Incredibly easy to move and retains it's position. Can be mounted on the edge of the table with the table bracket or on the table by using just the turning flange.</p>		
-------	---	--	---

Product Catalogue 2023-07-01



Art. Nr.

7.4. OUTSIDE SUPPORT. Super-P Extraction-Arms. All Parts Powder coated. Diameter 110/160mm. Length 1.5-4m.

P-349	Super-P Powder Coated Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.25+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.110mm</p>  <p>Straight Hood Super-P 1.5-4m</p>
P-350	Super-P powder Coated Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.5+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-351	Super-P Powder Coated Extraction-Arm with "Straight Hood" d.110mm/2m (0.25+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-352	Super-P Powder Coated Extraction-Arm with "Straight Hood" d.110mm/2m (0.5+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-353	Super-P Powder Coated Extraction-Arm with "Straight Hood" d.110mm/3m (0.5+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position		
P-354	Super-P Powder Coated Extraction-Arm with "Straight Hood" d.110mm/4m (0.5+0.6+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		


Product Catalogue 2023-07-01

Art. Nr.

P-355	Super-P Powder Coated Extraction-Arm with "67° Hood" d.110mm/1.5m (0.25+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.110mm</p>  <p>67° Hood Super-P 1.5-4m</p>
P-356	Super-P Powder Coated Extraction-Arm with "67° Hood" d.110mm/1.5m (0.5+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-357	Super-P Powder Coated Extraction-Arm with "67° Hood" d.110mm/2m (0.25+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-358	Super-P powder Coated Extraction-Arm with "67° Hood" d.110mm/2m (0.5+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-359	Super-P Powder Coated Extraction-Arm with "67° Hood" d.110mm/3m (0.5+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-360	Super-P Powder Coated Extraction-Arm "67° Hood" d.110mm/4m (0.5+0.6+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-361	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/1.5m (0.25+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.	 <p>150° Hood Super-P 1.5-4m</p>	


Product Catalogue 2023-07-01

Art. Nr.

P-362	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/1.5m (0.5+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.110mm</p>  <p>150° Hood Super-P 1.5-4m</p>
P-363	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/2m (0.25+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-364	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/2m (0.5+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-365	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/3m (0.5+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-366	Super-P Powder Coated Extraction-Arm with "150° Hood" d.110mm/4m (0.5+0.6+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-184	Super-P Powder Coated Extraction-Arm with d.160mm/1.5m (0.25+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-185	Super-P Powder Coated Extraction-Arm d.160mm/1.5m (0.5+1.5m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		

Product Catalogue 2023-07-01


Art. Nr.

P-186	Super-P Powder Coated Extraction- Arm d.160mm/2m (0.25+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.160mm</p>  <p>Super-P 1.5-4m</p>
P-187	Super-P Powder Coated Extraction- Arm d.160mm/2m (0.5+2m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-188	Super-P Powder Coated Extraction- Arm d.160mm/3m (0.5+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-189	Super-P Powder Coated Extraction-Arm d.160mm/4m (0.5+0.6+3m). Sealed Tube Ends. Incl. Wall bracket, hose and hood with plastic damper. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-486	Tight Damper for "Straight Hood" d.110mm. Made of powder coated steel sheet.		
P-485	Tight Damper for "67° Hood" and "150° Hood" d.110mm. Made of powder coated steel sheet.		
P-487	Tight Damper for "d.160mm" Hood. Made of powder coated steel sheet.		

Product Catalogue 2023-07-01


Art. Nr.

**7.5 OUTSIDE SUPPORT. Super-PM
 Extraction Arms. Hood and Handle of
 Stainless Steel. All other Parts Powder
 Coated. Dia. 110/160mm. Length 1.5m-4m.**

P-723	Super-PM Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.25+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.110mm</p>  <p><i>Straight Hood</i> Super-PM 1.5-4m</p>
P-724	Super-PM Extraction-Arm with "Straight Hood" d.110mm/1.5m (0.5+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-725	Super-PM Extraction-Arm with "Straight Hood" d.110mm/2m (0.25+2m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-726	Super-PM Extraction-Arm with "Straight Hood" d.110mm/2m (0.5+2m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-727	Super-PM Extraction-Arm with "Straight Hood" d.110mm/3m (0.5+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-728	Super-PM Extraction-Arm with "Straight Hood" d.110mm/4m (0.5+0.6+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		


Product Catalogue 2023-07-01

Art. Nr.

P-729	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/1.5m (0.25+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		<p>D.110mm</p>  <p>67° Hood Super-PM 1.5-4m</p>
P-730	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/1.5m (0.5+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-731	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/2m (0.25+2m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-732	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/2m (0.5+2m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-733	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/3m (0.5+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-734	<p>Super-PM Extraction-Arm with "67° Hood" d.110mm/4m (0.5+0.6+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		


Product Catalogue 2023-07-01

Art. Nr.

P-735	<p>Super-PM Extraction-Arm with "150° Hood" d.110mm/1.5m (0.25+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		<p>D.110mm</p>  <p>150° Hood Super-PM 1.5-4m</p>
P-736	<p>Super-PM Extraction-Arm with "150° Hood" d.110mm/1.5m (0.5+1.5m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-737	<p>Super-PM Extraction-Arm "150° Hood" d.110mm/2m (0.25+2m). Hood and Handle made of mirror polished acidproof stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-738	<p>Super-PM Extraction-Arm with "150° Hood" d.110mm/2m (0.5+2m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-739	<p>Super-PM Extraction-Arm with "150° Hood" d.110mm/3m (0.5+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		
P-740	<p>Super-PM Extraction-Arm with "150° Hood" d.110mm/4m (0.5+0.6+3m). Hood and Handle made of mirror polished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.</p>		

Product Catalogue 2023-07-01





Art. Nr.

P-741	Super-PM Extraction-Arm with "45° Hood" d.160/1.5m (0.25+1.5m). Hood and Handle made of mirrorpolished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position		
P-742	Super-PM Extraction-Arm with "45° Hood" d.160/1.5m (0.5+1.5m). Hood and Handle made of mirrorpolished acidproof Stainless Steel. All other Parts powder coated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-743	Super-PM Extraction-Arm with "45° Hood" d.160/2m (0.25+2m). Hood and Handle made of mirrorpolished acidproof stainless Steel. All other Parts powdercoated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		<p>D.160mm</p>  <p>Super-PM 1,5-4m</p>
P-744	Super-PM Extractor Arm with "45° Hood" d.160/2m (0.5+2m). Hood and Handle made of mirrorpolished acidproof stainless Steel. All other Parts powdercoated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-745	Super-PM Extractor Arm d.160/3m (0.5+3m). Hood and Handle made of mirrorpolished acidproof stainless Steel. All other Parts powdercoated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-746	Super-PM Extractor Arm d.160/4m (0.5+0.6+3m). Hood and Handle made of mirrorpolished acidproof stainless Steel. All other Parts powdercoated. Tight Tube Ends. Incl. Wall bracket, hose and hood. External hydraulically suspended parallelogram arms. "Free flow in the hose". Incredibly easy to move and stays in position.		
P-483	Tight Damper for "Straight Hood" d.110mm. Made of acidproof stainless Steel.		
P-482	Tight Damper for "67° Hood" and "150° Hood" d.110mm. Made of acidproof stainless Steel.		
P-484	Tight Damper for "d.160mm" Hood. Made of acidproof stainless Steel.		

Product Catalogue 2023-07-01




Art. Nr.

7.7 Extraction-Tables and Filter-Tables for Dust, Fume and Gases.

P-784	<p>K-Mesa 1m(W)x1m(D) Backdraft Extraction-Table. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Measure 1mx1m. Connection to extraction diameter 199mm outside. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>Without Filter/Fan</p> 
P-785	<p>K-Mesa 1.4m(W)x1m(D) Backdraft Extraction-Table. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Measure 1.4mx1m. Connection to extraction 2x diameter 199mm outside. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>Without Filter/Fan</p> 
P-786	<p>MK-Mesa 1m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with a table top of 75mm wide u-formed iron bars and 15mm slots in between, 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built-in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Measure 1mx1m. Connection for extraction diameter 199mm outside.</p>		<p>Without Filter/Fan</p> 
P-787	<p>MK-Mesa 1.4m Backdraft/Downdraft Table prepared for Extraction Arm. Incl. extraction table with a table top of 75mm wide u-formed iron bars and 15mm slots in between, 2 dust drawers, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings and a built-in regulating damper. Prepared for extraction arm. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Measure 1.4mx1m. Connection for extraction 2x diameter 199mm outside.</p>		<p>Without Filter/Fan</p> 




Product Catalogue 2023-07-01

Art. Nr.

<p>P-989</p>	<p>FK-Mesa F9/1m(W) Backdraft Filter-Table. F9 Filter Box 10m2. Table 1m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. F9 Filter Box (10M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With F9 Filter/Fan</p> 
<p>P-990</p>	<p>FK-Mesa HEPA/1m(W) Backdraft Filter-Table. HEPA H13 Filter Box (9m2). Table 1m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. HEPA H13 Filter Box (9m2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With HEPA Filter/Fan</p> 
<p>P-991</p>	<p>FK-Mesa AC/1m(W) Backdraft Filter-Table. Active Carbon Filter Cartridge 15Ltr/7kg. Table 1m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. Active Carbon Filter Cartridge 15Ltr/7kg, Fan 1-Phase/ 1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With Active Carbon Filter 15Ltr and Fan</p> 

Product Catalogue 2023-07-01

Art. Nr.


P-992	<p>FK-Mesa F9/1.4m(W) Backdraft Filter-Table. F9 Filter Box 10m2. Table 1.4m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. F9 Filter Box (10M2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With F9 Filter/Fan</p> 
P-993	<p>FK-Mesa HEPA/1.4m(W) Backdraft Filter-Table. HEPA H13 Filter Box (9m2). Table 1.4m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. HEPA H13 Filter Box (9m2), Fan 1-Phase/1.1Kw/220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With HEPA/Fan</p> 
P-994	<p>FK-Mesa AC/1.4m(W) Backdraft Filter-Table. Active Carbon Filter Cartridge 15Ltr/7kg. Table 1.4m(W)x1m(D)x3mm. Fan 1-Phase/1.1kW/220V/50Hz. Incl. table, legs, side panels possible to open, backdraft box with funnel-shaped vertical openings with horizontal "Guillotine" regulating dampers. Active Carbon Filter Cartridge 15Ltr/7kg, Fan 1-Phase/ 1.1Kw/ 220V/50 Hz, Circuit Breaker with overload protection and 4m Cable with Plug. Table, legs and side panels of 3mm steel-sheet. Backdraft box of 2mm steel-sheet. Powder painted white. Adjustable height 800-950mm. Prepared for 1.5m/2m/3m d.160mm Table Extraction-Arm (To be ordered separately).</p>		<p>With Active Carbon Filter 15Ltr and Fan</p> 
P-778	Spark Trap for K-Mesa/MK-Mesa 1m. 2 pcs.		
P-779	Spark Trap for K-Mesa/MK-Mesa 1.4m. 2 pcs.		
P-788	Flexi FLB 1,5m Extraction Arm White. Dia160mm.		
P-789	Flexi FLB 2m Extraction Arm White. Dia 160mm.		
P-790	Flexi FLB 3m Extraction Arm White. D.160mm.		

Product Catalogue 2023-07-01

Art. Nr.

8. DENTIST MOBILE EXTRACTOR-FILTERS.





8.1 Denta-Flex 400. Extractor-Filter with d.100mm/1.3m Extraction-Arm.

P-958	<p>Denta-Flex 400. Extractor-Filter with d.100mm/1.3m Extraction-Arm and a Transparent Hood. Incl. powder coated steel sheet filter box, EC Fan 1-phase/0.178kW /220V/50Hz, Pre-Filter F5/G4, HEPA H14 Filter (8 m2), Active Coal Filter Fleece, Adjustable Speed, 4 Castors with Brakes, Flexa Extraction-Arm d.100mm/1.3m with Transparent Hood, 4 m Cable with Plug. Measurements 360 mm(W)x470 mm(D) x900 mm(H) +Extraction-Arm 1.3m.</p>		
P-954	<p>Replacement HEPA H14 Filter (8m2) for Fika-Flex, Denta-Flex and Labbe 400. 305x305x20mm EN 1822(99.995%). With Certificate/Leak-Test</p>		
P-953	<p>Replacement Active Coal Filter (Set of 5 pcs) for Fika-Flex, Denta-Flex and Labbe 400. 300x300x15mm</p>		
P-995	<p>Replacement F5/G4 Pre-Filter for Fika-Flex and Denta-Flex.</p>		

Product Catalogue 2023-07-01

Art. Nr.



9. VIRUS/BACTERIA AIR PURIFIERS for Coffe-, Meeting-, Office and Waiting Rooms.

9.1 VBF-OFFICE. HEPA H14 Virus/Bacteria Airpurifier. Traditional Model.			
P-898	VBF-Office/700 HEPA-H14. EC 1-phase, 220V, 50/60Hz,175W. HEPA-H14(8M2) EN 1822 (99.995%). Prefilter F5/G4.ISO COARE 70% 4X125mm Castors with Brakes. 570(W)x610(D)x1100(H)		
P-899	VBF-Office/1000 HEPA-H14. EC 1-phase, 220V, 50/60Hz,350W. HEPA-H14(13m2) EN 1822 (99.995%). Prefilter F5/G4. ISO COARE 70% 4X125mm Castors with Brakes. 520(W)x610(D)x1325(H).		
P-800	Replacement Prefilter for all VBF-700 Models. F5/G4.ISO COARE 70% 457x457x50mm.		
P-801	Replacement Prefilter for all VBF-1000 Models. F5/G4.ISO COARE 70% 457x457x100mm.		
P-802	Replacement HEPA H14 (8M2) for all VBF-700 Models. EN 1822 (99.995%) With Certificate and Leak Tested. 457x457x100mm.		

Tel: +46 40 70015 Fax: +46 40 30 26 92 E-mail: info@plymoth.com

Product Catalogue 2023-07-01


Art. Nr.

P-803	Replacement HEPA H14 (13m ²) for all VBF-1000 Models. EN 1822 (99.995%) With Certificate and Leak Tested. 457x457x150mm		
P-580	Legs 4x125mm for all VBF-700/1000 Models.		

Product Catalogue 2023-07-01

Art. Nr.

**9.2 Fika-Flex 500. “Clean-Air Shower”.
 Immediately 99.995% Clean Air “Where
 People meet”.**


P-955	<p>Fika-Flex 400. “Clean-Air Shower” with horizontally moveable Steel Diffusion Hood (1m/d.160mm) Incl. powder coated steel sheet filter box, EC Fan 1-phase/178W/220V/50Hz, Pre-Filter F5/G4, HEPA H14 Filter (8 m²), Active Coal Filter Fleece, Adjustable Speed, 4 Castors with Brakes, 4 m Cable with Plug. Measurements 360 mm(W)x470 mm(D) x900 mm(H) + Diffusion-Arm (1m+1m).</p>		
P-953	<p>Replacement Active Coal Filter (Set of 5 pcs) for Fika-Flex, Denta-Flex and Labbe 400. 300x300x15mm</p>		
P-954	<p>Replacement HEPA H14 Filter (8m²) for Fika-Flex, Denta-Flex and Labbe 400. 305x305x20mm EN 1822(99.995%). With Certificate/Leak-Test</p>		
P-995	<p>Replacement F5/G4 Pre-Filter for Fika-Flex and Denta-Flex.</p>		

Product Catalogue 2023-07-01

Art. Nr.



10. EXHAUST-GAS REELS, HOSES, NOZZLES, FANS AND HORIZONTAL SUSPENSION ARMS.

10.1 Exhaust-Gas Reels. Drum width 475/650/1000/1250mm. Without Hose.

P-569	Hose Reel with Drum Width 475 mm. Hose not included. Spring operated hose reel with locking mechanism. Hoses from d.100-150 mm can be used.		 Hose Reel without Hose
P-254	Hose Reel with Drum Width 650 mm. Hose not included. Spring operated hose reel with locking mechanism. Hoses from d.100-150 mm can be used.		
P-441	Hose Reel with Drum Width 1000 mm. Hose not included. Spring operated hose reel with locking mechanism. Hoses from d.100-150 mm can be used.		
P-442	Hose Reel with Drum Width 1250 mm. Hose not included. Spring operated hose reel with locking mechanism. Hoses from d.100-150 mm can be used.		

Product Catalogue 2023-07-01

Art. Nr.

10.2 Wall bracket for 1 or 2 Exhaustgas Hoses Dia. 75/100/125/150mm. Without Hose.			
P-197	Wall bracket for one d.75 mm Exhaust Hose Incl. Wall bracket with one d.75 mm inlet for one exhaust hose. Hose not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		 <p>Wallbracket for Exhaust Hose(s)</p>
P-198	Wall bracket for two d.75 mm Exhaust Hoses Incl. Wall bracket with two d.75 mm inlets for exhaust hoses. Hoses not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-199	Wall bracket for one d.100 mm Exhaust Hose Incl. Wall bracket with one d.100 mm inlet for one exhaust hose. Hose not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-207	Wall bracket for two d.100 mm Exhaust Hoses Incl. Wall bracket with two d.100 mm inlets for exhaust hoses. Hoses not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-208	Wall bracket for one d.125 mm Exhaust Hose Incl. Wall bracket with one d.125 mm inlet for one exhaust hose. Hose not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-209	Wall bracket for two d.125 mm Exhaust Hoses Incl. Wall bracket with two d.125 mm inlets for exhaust hoses. Hoses not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-212	Wall bracket for one or two d.150 mm Exhaust Hoses Incl. Wall bracket with two d.150 mm inlets for exhaust hoses. Hoses not included. (P-Max fan can be mounted directly on top of the Wall bracket.)		
P-230	Hose Holder. To be mounted directly on the side of the Wall bracket or on the wall. For hoses with a d. of up to 150mm.		 <p>Hose Holder</p>

Product Catalogue 2023-07-01

Art. Nr.

10.3 EPDM Rubber Exhaust-Gas Hose D.100/125/150mm. Length 7.5m or 10m.			
P-046	Exhaust EPDM Rubber Hose d.100 mm / 7.5 m + 2 Hose Clamps		
P-047	Exhaust EPDM Rubber Hose d.100 mm / 10 m + 2 Hose Clamps		
P-048	Exhaust EPDM Rubber Hose d.125 mm / 7.5 m + 2 Hose Clamps		
P-049	Exhaust EPDM Rubber Hose d.125 mm / 10 m + 2 Hose Clamps		
P-445	Exhaust EPDM Rubber Hose d.150 mm / 7.5 m + 2 Hose Clamps		
P-446	Exhaust EPDM Rubber Hose d.150 mm / 10 m + 2 Hose Clamps		
P-490	Hose Stop for Hose Reel d.100mm.		
P-491	Hose Stop for Hose Reel d.125mm.		
P-492	Hose Stop for Hose Reel d.150mm.		

Product Catalogue 2023-07-01


Art. Nr.

**10.4 Nozzles for Dia. 100/125/150mm Hose.
 Nozzleopening Dia 150mm.**

P-216	Exhaustgas Nozzle-Steel d.100/150mm with test Opening. Incl. nozzle made of steel sheet with d.100mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-217	Exhaustgas Nozzle-Steel d.125/150mm with test Opening. Incl. nozzle made of steel sheet with d.125mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-218	Exhaustgas Nozzle-Steel d.150/150mm with test Opening. Incl. nozzle made of steel sheet with d.150mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-220	Exhaustgas Nozzle-EPDM Rubber covered d.100/150mm with test Opening. Incl. nozzle covered of EPDM rubber with d.100mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-221	Exhaustgas Nozzle-EPDM Rubber covered d.125/150mm with test Opening. Incl. nozzle covered of EPDM rubber with d.125mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-222	Exhaustgas Nozzle-EPDM Rubber covered d.150/150mm with test Opening. Incl. nozzle covered of EPDM rubber with d.150mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		
P-215	Exhaustgas Nozzle-EPDM Rubber covered d.75/150mm with test Opening. Incl. nozzle covered of EPDM rubber with d.75mm opening in one side (for the connection of the exhaustgas hose) and d.150mm opening at the other side with automatically closing rubber lid. Test opening 20x40mm with automatically closing rubber cover.		



Product Catalogue 2023-07-01

Art. Nr.

10.5 Fans for Reels and Wall brackets.			
P-033	Fan mounting Bracket for Hose Reels. Incl. bracket made of steel sheet for mounting on the outlet side of the hose reel, 4 pcs. M8/16mm bolts with nuts and 8pcs. M8/16mm bolts for mounting the fan on the bracket.		
P-011	P-Max Fan 0.37 kW/3-Phase/1300m3 freeblowing/ 230V/380-420V/50Hz/440V/60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes and Exhaustgas-Hose Reels.		
P-012	P-Max Fan 0.75 kW/3-Phase/2100m3 freeblowing/ 230V/380-420V /50Hz/ 440V /60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes and Exhaustgas-Hose Reels.		
P-013	P-Max Fan TURBO 0.75 kW/3-Phase/2100m3 /230V/380-420V /50Hz/440V/60Hz. <i>Must not be run freeblowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose Reels.		 P-Max Fans
P-032	P-Max Fan 1.1 kW/3-Phase/2100m3 freeblowing/230V/380-420V/50Hz/440V/60Hz. Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose Reels.		
P-122	V-Max Fan without Support Bracket and Inlet/1.1 kW/3-Phase/3000m3 freeblowing /230V/380-420V /50Hz/440V/60Hz. Incl. fan case, motor and outlet 145/220mm. For mounting directly on the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose-Wall brackets. For mounting on Fan Brackets for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose Reels.		
P-015	P-Max Fan TURBO 0.75 kW/1-Phase/2100m3/ 220V/50Hz. <i>Must not be run freeblowing!</i> Incl. fan case, motor and d.200mm outlet (inside measure). For mounting directly on to the Wall bracket of Flexi- and Super-Max SMSV Extractor Arms and Exhaust-hose Wall brackets. For mounting on Fanbracket for Extractor-Cranes, Wall-Flex and Exhaustgas-Hose Reels.		





Product Catalogue 2023-07-01

Art. Nr.

10.6 Horizontal Suspension Arms 2-8m for Reels and Wall brackets. Not for Lifting.			
P-157	H-Flex Suspension Arm 2 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 2 m suspension arm with ball bearings (1.3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 2 m is prepared for 30/30/10/2 mm C-profile (P-027).		 <p>H-Flex 2-3.7 m</p>
P-158	H-Flex Suspension Arm 3 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 3 m suspension arm with ball bearings (2.3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 3 m is prepared for 30/30/10/2 mm C-profile (P-028).		
P-159	H-Flex Suspension Arm 3.7 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 3.7 m suspension arm with ball bearings (3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 3.7 m is prepared for 30/30/10/2 mm C-profile (P-029).		
P-156	Herkules Suspension Arm 0.5m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 0.5m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		 <p>Herkules 0.5-4 m</p>
P-193	Herkules Suspension Arm 1m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 1m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		
P-194	Herkules Suspension Arm 2m/200 kg. <i>Not for lifting!</i> Incl.Wall bracket with disc brake, 2m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		

Product Catalogue 2023-07-01

Art. Nr.

P-195	Herkules Suspension Arm 3m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 3m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		 Herkules 0.5-4 m
P-190	Herkules Suspension Arm 4m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 4m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		
P-027	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 1.3m. Incl. C-profile 30/30/10/2mm L. 820mm with 3 M10/90mm bolts and nuts.		
P-028	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 2.3m. Incl. C-profile 30/30/10/2mm L. 1870mm with 6 M10/90mm bolts and nuts.		
P-029	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 3m. Incl. C-profile 30/30/10/2mm L. 2570mm with 8 M10/90mm bolts and nuts.		
P-023	Suspension Trolley with 4 Ball Bearing Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 60 kg weight (not for lifting). Incl. trolley with 4 ball bearing wheels.		
P-024	Suspension Trolley with plastic Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 10 kg weight (not for lifting). Incl. trolley with 2 plastic wheels, S-hook and a sling.		

Product Catalogue 2023-07-01


Art. Nr.

10.7 Hose Sets for Horizontal Suspension Arms.		
P-472	Hose Set d. 125mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Incl. 2.3 m d.125mm hose, 2 hose clamps, 3 hose bands and one d.125mm hose connection.	
P-449	Hose Set d. 160mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Incl. 2.3 m d.160mm hose, 2 hose clamps, 3 hose bands and one d.160mm hose conn.	
P-473	Hose Set d. 200mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Incl. 2.3 m d.200mm hose, 2 hose clamps, 3 hose bands and one d.200mm hose conn.	
P-474	Hose Set d. 125mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.125mm hose, 2 hose clamps, 4 hose bands and one d.125mm hose conn.	
P-448	Hose Set d. 160mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.160mm hose, 2 hose clamps, 4 hose bands and one d.160mm hose conn.	
P-475	Hose Set d. 200mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.200mm hose, 2 hose clamps, 4 hose bands and one d.200mm hose conn.	
P-476	Hose Set d. 125mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.125mm hose, 2 hose clamps, 5 hose bands and one d.125mm hose connection.	
P-447	Hose Set d. 160mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.160mm hose, 2 hose clamps, 5 hose bands and one d.160mm hose connection.	
P-477	Hose Set d. 200mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.200mm hose, 2 hose clamps, 5 hose bands and one d.200mm hose connection.	
P-478	Hose Set d. 125mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.125mm hose, 2 hose clamps, 5 hose bands and one d.125mm hose connection.	320,-
P-191	Hose Set d. 160mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.160mm hose, 2 hose clamps, 5 hose bands and one d.160mm hose connection.	310,-
P-479	Hose Set d. 200mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.200mm hose, 2 hose clamps, 5 hose bands and one d.200mm hose connection.	360,-



Product Catalogue 2023-07-01



Art. Nr.

P-480	Hose Set d. 125mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.125mm hose, 2 hose clamps, 6 hose bands and one d.125mm hose connection.		 Extension Hose
P-450	Hose Set d. 160mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.160mm hose, 2 hose clamps, 6 hose bands and one d.160mm hose connection.		
P-481	Hose Set d. 200mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.200mm hose, 2 hose clamps, 6 hose bands and one d.200mm hose connection.		

Product Catalogue 2023-07-01


Art. Nr.

11. Horizontal Suspension Arms. 0.5m-8m.

11.1 SINGLE ARM. Horizontal Suspension Arms. Not for Lifting!			
P-153	H-Max Suspension Arm 1.3m/100kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, horizontal steel arm 1.3m with ball bearings and suspension shackle with turning joint. Prepared for c-profile (30/30/10/2mm) (P-027).		 <p>H-Max 1.3-3 m</p>
P-154	H-Max Suspension Arm 2.3m/100kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, horizontal steel arm 2.3m with ball bearings and suspension shackle with turning joint. Prepared for c-profile (30/30/10/2mm) (P-028).		
P-155	H-Max Suspension Arm 3m/100kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, horizontal steel arm 3m with ball bearings and suspension shackle with turning joint. Prepared for c-profile (30/30/10/2mm) (P-029).		
P-157	H-Flex Suspension Arm 2 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 2 m suspension arm with ball bearings (1.3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 2 m is prepared for 30/30/10/2 mm C-profile (P-027).		 <p>H-Flex 2-3.7 m</p>
P-158	H-Flex Suspension Arm 3 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 3 m suspension arm with ball bearings (2.3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 3 m is prepared for 30/30/10/2 mm C-profile (P-028).		
P-159	H-Flex Suspension Arm 3.7 m / 80 kg. <i>Not for lifting!</i> Wall bracket with disc brake, 3.7 m suspension arm with ball bearings (3 m + 0.7 m) and mounting bracket in the end. A hose reel, a Wall bracket with exhaust hose or a Flexi extractor arm can be mounted in the end of the suspension arm. H-Flex 3.7 m is prepared for 30/30/10/2 mm C-profile (P-029).		

Product Catalogue 2023-07-01


Art. Nr.

P-156	Herkules Suspension Arm 0.5m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 0.5m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		 Herkules 0.5-4 m
P-193	Herkules Suspension Arm 1m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 1m frame structure steel suspension arm with ball bearings and 3-way bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		
P-194	Herkules Suspension Arm 2m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 2m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		
P-195	Herkules Suspension Arm 3m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 3m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		
P-190	Herkules Suspension Arm 4m/200 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, 4m frame structure steel suspension arm with ball bearings and 3-way mounting bracket in the end. C-profile 30/30/10/2mm along the bottom side of the arm. Herkules can carry two "9m Extractor Cranes" or one "H-Flex Suspension Arm 3.7m with an Exhaustgas Hose Reel" or two "H-Flex Suspension Arms 3.7m with Wall bracket for Exhaustgas Hose".		

Product Catalogue 2023-07-01



Art. Nr.

11.2 DOUBLE ARM. Horizontal Suspension Arms. Not for Lifting!

P-451	HH-Flex 1.9m with two Horizontal steel Arms (1.3+0.6m). Max. 40 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 40kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		 <p>HH-Flex 1.9-5.6 m</p>
P-452	HH-Flex 2.3m with two Horizontal steel Arms (1.3+1m). Max. 25 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 25kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		
P-453	HH-Flex 2.9m with two Horizontal steel Arms (2.3+0.6m). Max. 40 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 40kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		
P-454	HH-Flex 3.3m with two Horizontal steel Arms (2.3+1m). Max. 25 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 25kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		
P-455	HH-Flex 3.6m with two Horizontal steel Arms (3+0.6m). Max. 30 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 30kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		
P-456	HH-Flex 4m with two Horizontal steel Arms (2,3+1.6m). Max. 20 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 20kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		
P-457	HH-Flex 4m with two Horizontal steel Arms (3+1m). Max. 25 kg. <u>Not for lifting!</u> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 25kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.		


Product Catalogue 2023-07-01

Art. Nr.

P-458	<p>HH-Flex 4.6m with two Horizontal steel Arms (3+1.6m). Max. 20 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 20kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.</p>		 <p>HH-Flex 1.9-5.6 m</p>
P-460	<p>HH-Flex 5.6m with two Horizontal steel Arms (3+2.6m). Max. 15 kg. <i>Not for lifting!</i> Incl. Wall bracket with disc brake, two horizontal steel arms with ball bearings and disc brakes. Shackle for max. 15kg in the end of the outer arm. Prepared for c-profile 30/30/10/2mm in the inner arm.</p>		
P-494	<p>Herko-Max 1.8m with two Horizontal steel Arms (0.5+1.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Max 1.3m. P-156 + P-153). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-495	<p>Herko-Max 2.8m with two Horizontal steel Arms (0.5+2.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Max 2.3m. P-156 + P-154). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-496	<p>Herko-Max 3.5m with two Horizontal steel Arms (0.5+3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Max 3m. P-156 + P-155). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		 <p>Herko-Max 1.8-7 m</p>
P-497	<p>Herko-Max 2.3m with two Horizontal steel Arms (1+1.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Max 1.3m. P-193 + P-153). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-498	<p>Herko-Max 3.3m with two Horizontal steel Arms (1+2.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Max 1.3m. P-193 + P-154). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-499	<p>Herko-Max 4m with two Horizontal steel Arms (1+3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Max 3m. P-193 + P-155). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.</p>		

Product Catalogue 2023-07-01

Art. Nr.

P-500	Herko-Max 3.3m with two Horizontal steel Arms (2+1.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Max 1.3m. P-194 + P-153). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-501	Herko-Max 4.3m with two Horizontal steel Arms (2+2.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 2m + H-Max 1.3m. P-194 + P-154). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-502	Herko-Max 5m with two Horizontal steel Arms (2+3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 2m + H-Max 3m. P-194 + P-155). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-503	Herko-Max 4.3m with two Horizontal steel Arms (3+1.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Max 1.3m. P-195 + P-153). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-504	Herko-Max 5.3m with two Horizontal steel Arms (3+2.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Max 1.3m. P-195 + P-154). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	 <p>Herko-Max 1.8-7 m</p>
P-505	Herko-Max 6m with two Horizontal steel Arms (3+3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Max 3m. P-195 + P-155). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-506	Herko-Max 5.3m with two Horizontal steel Arms (4+1.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Max 1.3m. P-190 + P-153). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-507	Herko-Max 6.3m with two Horizontal steel Arms (4+2.3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Max 1.3m. P-190 + P-154). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	
P-508	Herko-Max 7m with two Horizontal steel Arms (4+3m). Max. 100 kg. <i>Not for lifting!</i> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Max 3m. P-190 + P-155). Max. 100 kg can be suspended in the end of the outer arm. Not for lifting.	

Product Catalogue 2023-07-01


Art. Nr.

P-510	Herko-Flex 2.5m with two Horizontal steel Arms (0.5+2m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Flex 2m. P-156 + P-157). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-511	Herko-Flex 3.5m with two Horizontal steel Arms (0.5+3m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Flex 3m. P-156 + P-158). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-512	Herko-Flex 4.2m with two Horizontal steel Arms (0.5+3.7m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 0.5m + H-Flex 3.7m. P-156 + P-159). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-513	Herko-Flex 3m with two Horizontal steel Arms (1+2m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Flex 2m. P-193 + P-157). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-514	Herko-Flex 4m with two Horizontal steel Arms (1+3m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Flex 3m. P-193 + P-158). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-515	Herko-Flex 4.7m with two Horizontal steel Arms (1+3.7m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 1m + H-Flex 3.7m. P-193 + P-159). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-516	Herko-Flex 4m with two Horizontal steel Arms (2+2m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 2m + H-Flex 2m. P-194 + P-157). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-517	Herko-Flex 5m with two Horizontal steel Arms (2+3m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 2m + H-Flex 3m. P-194 + P-158). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		
P-518	Herko-Flex 5.7m with two Horizontal steel Arms (2+3.7m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 2m + H-Flex 3.7m. P-194 + P-159). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.		



Product Catalogue 2023-07-01

Art. Nr.

P-519	<p>Herko-Flex 5m with two Horizontal steel Arms (3+2m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Flex 2m. P-195 + P-157). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		 <p>Herko-Flex 2.5-7.7 m</p>
P-520	<p>Herko-Flex 6m with two Horizontal steel Arms (3+3m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Flex 3m. P-195 + P-158). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-521	<p>Herko-Flex 6.7m with two Horizontal steel Arms (3+3.7m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 3m + H-Flex 3.7m. P-195 + P-159). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-522	<p>Herko-Flex 6m with two Horizontal steel Arms (4+2m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Flex 2m. P-190 + P-157). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-523	<p>Herko-Flex 7m with two Horizontal steel Arms (4+3m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Flex 3m. P-190 + P-158). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		
P-524	<p>Herko-Flex 7.7m with two Horizontal steel Arms (4+3.7m). Max. 80 kg. <u>Not for lifting!</u> Incl. two horizontal steel arms with Wall brackets, disc brakes and ball bearings (Herkules 4m + H-Flex 3.7m. P-190 + P-159). Max. 80 kg can be suspended in the end of the outer arm. Not for lifting.</p>		

Product Catalogue 2023-07-01

Art. Nr.

11.3 Hose Sets for Horizontal Suspension Arms. Dia. 125/160/200mm.		
P-472	Hose Set d. 125mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.125mm hose, 2 hose clamps, 3 hose bands and one d.125mm hose connection.	
P-449	Hose Set d. 160mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.160mm hose, 2 hose clamps, 3 hose bands and one d.160mm hose connection.	
P-473	Hose Set d. 200mm/2.3m for Herkules 0.5m and 1m Suspension Arms. Set of 2.3 m d.200mm hose, 2 hose clamps, 3 hose bands and one d.200mm hose connection.	
P-474	Hose Set d. 125mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.125mm hose, 2 hose clamps, 4 hose bands and one d.125mm hose connection.	
P-448	Hose Set d. 160mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.160mm hose, 2 hose clamps, 4 hose bands and one d.160mm hose connection.	
P-475	Hose Set d. 200mm/3.3m for H-Flex 2m Suspension Arm or HH-Flex/2-2.3m Suspension Arms or Herkules 2m Suspension Arm. Incl. 3.3m d.200mm hose, 2 hose clamps, 4 hose bands and one d.200mm hose connection.	
P-476	Hose Set d. 125mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.125mm hose, 2 hose clamps, 5 hose bands and one d.125mm hose connection.	
P-447	Hose Set d. 160mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.160mm hose, 2 hose clamps, 5 hose bands and one d.160mm hose connection.	
P-477	Hose Set d. 200mm/4m for H-Flex 3m Suspension Arm or HH-Flex/3-3.5m Suspension Arms or Herkules 3m Suspension Arm. Incl. 4m d.200mm hose, 2 hose clamps, 5 hose bands and one d.200mm hose connection.	
P-478	Hose Set d. 125mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.125mm hose, 2 hose clamps, 5 hose bands and one d.125mm hose connection.	



Product Catalogue 2023-07-01



Art. Nr.

P-191	Hose Set d. 160mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.160mm hose, 2 hose clamps, 5 hose bands and one d.160mm hose connection.		 Extension Hose
P-479	Hose Set d. 200mm/5m for H-Flex 3,7m Suspension Arm or HH-Flex/4-4.5m Suspension Arms or Herkules 4m Suspension Arm. Incl. 5m d.200mm hose, 2 hose clamps, 5 hose bands and one d.200mm hose connection.		
P-480	Hose Set d. 125mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.125mm hose, 2 hose clamps, 6 hose bands and one d.125mm hose connection.		
P-450	Hose Set d. 160mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.160mm hose, 2 hose clamps, 6 hose bands and one d.160mm hose connection.		
P-481	Hose Set d. 200mm/6m for HH-Flex/5-5.6m Suspension Arms. Incl. 6m d.200mm hose, 2 hose clamps, 6 hose bands and one d.200mm hose connection.		

Product Catalogue 2023-07-01

Art. Nr.

11.4 C-Profiles and Suspension Trolleys for Horizontal Suspension Arms.

P-027	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 1.3m. Incl. C-profile 30/30/10/2mm L. 820mm with 3 M10/90mm bolts and nuts.		
P-028	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 2.3m. Incl. C-profile 30/30/10/2mm L. 1870mm with 6 M10/90mm bolts and nuts.		
P-029	C-Profile 30/30/10/2mm for Extractor-Cranes and Suspension Arms which have a first Horizontal Support Arm with a length of 3m. Incl. C-profile 30/30/10/2mm L. 2570mm with 8 M10/90mm bolts and nuts.		
P-023	Suspension Trolley with 4 Ball Bearing Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 60 kg weight (not for lifting). Incl. trolley with 4 ball bearing wheels.		
P-024	Suspension Trolley with plastic Wheels for C-Profile 30/30 mm and Herkules Suspension Arms. Max. 10 kg weight (not for lifting). Incl. trolley with 2 plastic wheels, S-hook and a sling.		